



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Autobag SPrint SidePouch Bagger



## At a Glance

- Up to 70 bags per minute in intermittent mode, up to 120 bags per minute in continuous mode
- Integrates with automatic infeed equipment, inline imprinters and existing production lines
- Safe and reliable system is quick to set-up and easy to operate
- Change bag sizes easily in less than 2 minutes
- Operator-friendly AutoTouch control software enhance system reliability and simplify the user experience
- Highly flexible, accommodates a wide variety of loading methods, automatic infeeds, inline imprinters, products, and bag sizes
- Improves bag packaging productivity and offers a rapid return on investment
- System-matched bags offer special features, such as reclosable zippers, resealable flaps, tamper-evident perforations and more

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Load Bags at 120 Bags per Minute

The SPrint SidePouch packaging system is engineered to provide high productivity solutions for hand load through fully-automatic packaging applications.

Operating at speeds up to 120 bags per minute in continuous mode, and offering special bag features, the SPrint bagger reduces operating costs while providing the widest range of industrial and retail bag packaging solutions.

The SPrint bagger presents a conveyor of pre-opened bags that are staged for immediate loading. A standard 60" load area provides ample space for one or more operators or infeeds, while the ergonomic design is preferred for its close proximity of product to the bag. Operator safety is enhanced by the modular design of the loading and sealing areas, with automatic bag sealing and trimming occurring away from the bag loading area. The SPrint is also available in a 30" load area configuration that provides a cost-effective alternative for lower volume applications, or production environments that require a smaller footprint. Both systems offer continuous or intermittent bag indexing to accommodate high-speed packaging of individual products or kits.

The SPrint bagging system installs quickly and requires minimal operator training and maintenance. The system can be integrated with a SPrint AutoLabel PI 412c Imprinter for inline imprinting, or with a variety of support conveyors and infeeds for semi- to fully-automatic packaging. The standard sealing unit ensures attractive, high quality bag seals for most industrial and retail applications, while the optional medical sealer meets the stringent sealing requirements of the health care industry. Bag changeover is fast and easy to accommodate short production runs, with a single box holding up to 5,000 bags to facilitate longer runs.

Genuine SidePouch bags are system-matched for optimum performance, and offer a variety of value-added features, such as reclosable zippers, resealable flaps, gussets, reinforced headers and easy-open perforations. Since the bags are pre-made, costly machine modifications are not needed to utilize these features. SidePouch bags are available in an assortment of materials that can be pre-printed with high-resolution graphics, text and bar codes for unique, attractive packaging with a competitive edge.

## Benefits

Safe and reliable packing machine is quick to set-up and easy to operate

Advances packaging productivity and offers a rapid return on investment

Operates at speeds up to 70 bags per minute in intermittent mode, and up to 120 bags per minute in continuous mode

Integrates with automatic infeed equipment, inline imprinters and existing production lines

System-matched bags offer special features, such as reclosable zippers, resealable plastic bags and more

## Typical Applications

Disposable health care & dental products

Cosmetics, health & beauty aids

Automotive replacement parts

Hardware, appliance & plumbing

Electrical and electronic products

Lawn & garden replacement parts

Spare parts kits

Pet supplies

Hobby & craft items

Printed manuals and inserts

Jewelry & novelty items

Medical device packaging

## Features of the SPrint

60" load area provides ample space for one or more operators or infeeds.

Operator-adjustable pass-through accommodates various product sizes.

Electronic sensing automatically indexes, trims and seals bags in intermittent or continuous modes.

Standard heat sealer assembly ensures high quality seals.

Bag tower assembly to simplify bag orientation and loading.

Footswitch for manual bag indexing.

## Options

30" Load area configuration

SPrint AutoLabel PI 412c in-line printer  
Flat and V-style product support conveyors  
Bag deflation  
Medical heat sealer assembly  
Anti-jam detection device  
Bag shaker  
Product support shelf  
Bag position sensor  
Spare parts kits  
Custom engineering & integration design and support

## Bag Specifications

Film thickness: 1.5 to 4.0 mil  
Width: 2.36" to 20"  
Length: 3" to 18"  
Pass-Through: Up to 5" (12.7 cm)

## Specifications of the SPrint 60V

Electrical: 115/230 VAC switchable 50/60 Hz  
Air Feed: 60 psi of clean, dry air  
Width: 168" (427 cm)  
Height: 36" (91 cm)  
Depth: 32" (81 cm)  
Weight: 400 lbs (181 kg)

## Specifications of the SPrint 30V

Electrical: 115/230 VAC switchable 50/60 Hz  
Air: 60 psi of clean, dry air  
30V Dimensions: 138"W x 32"D x 36"H (351cm x 81cm x 91cm)  
60V Dimensions: 168"W x 32"D x 36"H (427cm x 81cm x 91cm)  
30V Weight: 375 lbs (170 kg)  
60V Weight: 400 lbs (181 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your bagging equipment.