



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Autobag 500 Bagging System



## At a Glance

- Easily integrates with inline printers, counters, scales, and conveyors
- Simple maintenance and repairs maximize uptime
- Simple changeover
- Control screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring
- Processor controlled servo motors, Ethernet-capable networking
- Flexible mechanical design streamlines integration
- Compact footprint minimizes floor space
- Simple height adjustment and casters for operator comfort and portability

Buy your [bags-on-a-roll](#) from us, and get a discount on this Autobag bagger!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Bagger Optimizes Reliability, Flexibility and Ergonomics

The Autobag 500 bagger is a technologically-advanced, automatic filling and sealing machine designed for reliability, flexibility and optimizing packaging throughput. Capable of cycling at rates over 100 bags per minute, this system was designed to maximize machine uptime while lowering total cost of ownership.

State-of-the-art engineering has led to an innovative, inherently safe design. No light curtains or bulky guarding are required to achieve safe operation for hand load operations. This revolutionary new approach provides unobstructed access to the open bag, facilitating faster, more ergonomic loading.

The system features a simple design with very few moving parts, reducing lifetime cost and improving uptime. Servo driven web controls along with job storage capabilities reduce the amount of bags in queue, eliminating waste and decreasing changeover time.

A straightforward, simple design with very few moving parts reduces lifetime cost and improves reliability, while on-board diagnostics and modular components simplify maintenance.

Flexibility has been built into the system, allowing the Autobag 500 to meet the needs of any packaging operation. The open design makes this bagger highly compatible with Autobag and third-party counters,

scales and infeeds. The Autobag 500 can also be networked to facilitate full pack station integration and central monitoring. When integrated with the AutoLabel 500 inline imprinter, a complete print-and-pack station is achieved.

When used with genuine [Autobag pre-opened bags-on-a-roll](#), the Autobag 500 ushers in the next evolution of high-quality, reliable and flexible bag packaging, backed by the industry's most comprehensive engineering and field service network.

## User Benefits

Easily integrates with inline printers, counters, scales, and conveyors for semi- to fully-automatic bagging

Modular components and dedicated service access simplify maintenance and repairs to maximize uptime

Multi-position unwind with tension control simplify changeover

AutoTouch Control Screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring

More bag size options; width 2" to 12", length 5" to 20" supported (36" long unsupported)

Processor controlled servo motors, Ethernet-capable networking, and flexible mechanical design streamline integration

Compact footprint minimizes floor space

Simple height adjustment and casters for operator comfort and portability

Adjustable pass-through up to 5" for maximum flexibility and packaging efficiency

## Typical Applications

Aerospace & defense

Apparel & accessory packaging

Automotive

Electronics

Hardware & fasteners

Healthcare

Hobby & craft

Household products

Personal products

Pet products

Toys

## Bag Specifications

Film thickness: 1.09 to 4.0 mil

Width: 2" to 12"

Length: 5" to 20"

Pass-Through: 5" (12.7 cm)

Bag Load Capacity: Up to 5 lbs (with load shelf)

## Specifications of the Autobag 500

Electrical: 110V to 240V VAC, 50/60 Hz

Power Consumption: 1500 Watts (VA) max

Air: 5 CFM/80 psi of clean, dry air

Dimensions: 37.6"W x 64.5"D x 37.1"-47.1"H (95.5cm x 163.8cm x 94.23-119.6cm)

Weight: 350 lbs (158 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your bagging equipment.