



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Autobag 550 Bagging System



At a Glance

- Next-bag-out printing prevents product queuing and reduces waste
- Simple changeover
- Consistent, high-quality seals
- Control screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring
- Processor controlled servo motors, Ethernet-capable networking, and flexible mechanical design streamline integration
- Compact footprint minimizes floor space
- Simple height adjustment and casters for operator comfort and portability
- Easily integrates with third-party systems for mail order fulfillment applications

Buy your [bags-on-a-roll](#) from us, and get a discount on this Autobag bagger!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

For Your Order Fulfillment, Short-Run and Build-on-Demand Operations

The Autobag 550 bagger is a technologically-advanced, automatic filling and sealing machine designed for reliability, flexibility and optimizing packaging throughput. Capable of cycling at speeds up to 45 bags per minute, this system was designed to maximize machine uptime while lowering total cost of ownership.

Next-bag-out printing is achieved with an advanced thermal transfer imprinter positioned directly over the next bag to be loaded. This ensures accuracy and efficiency in applications that require frequent product and label changeovers, prevents product queuing and eliminates a separate labeling operation.

State-of-the-art engineering has led to an inherently safe and flexible design. No light curtains or double palm switches are required to achieve safe hand-load operation. The Autobag 550 is configurable for left- or right-hand access to the HMI, cycle switch, and ribbon and bag loading areas, improving ergonomics and operator productivity. Plus, the Autobag 550 can be networked to facilitate full pack station integration and central monitoring. A 45 degree tilt option is available for orienting long or delicate products.

A straightforward, simple design with very few moving parts reduces lifetime cost and improves reliability, while on-board diagnostics and modular components simplify maintenance.

Flexibility has been built into the system allowing the Autobag 550 to meet the needs of any loading area. Capable of being configured for left or right-hand access to the HMI, cycle switch, roll loading, and ribbon loading provides seamless integration into any operation. The system can also be networked for full pack station integration to facilitate central monitoring; and the extraction of productivity information that can be manipulated for detailed analysis.

When used with genuine [Autobag pre-opened bags-on-a-roll](#), the Autobag 550 ushers in the next evolution of high-quality, reliable and flexible bag packaging, backed by the industry's most comprehensive engineering and field service network.

User Benefits

Next-bag-out printing prevents product queuing and reduces waste

Multi-position unwind with tension control simplify changeover

Newly designed bag sealer area combined with improved temperature control and optional seal-flatteners ensure consistent, high-quality seals

AutoTouch Control Screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring

Processor controlled servo motors, Ethernet-capable networking, and flexible mechanical design streamline integration

More bag size options; width 2" to 12", length 5" to 20" supported (36" long unsupported)

Compact footprint minimizes floor space

Simple height adjustment and casters for operator comfort and portability

Easily integrates with third-party systems for mail order fulfillment applications

Modular components and dedicated service access simplify maintenance and repairs to maximize uptime

Adjustable pass-through up to 5" for maximum flexibility and packaging efficiency

Typical Applications

Mail Order and ecommerce fulfillment

Ecommerce fulfillment

Prescription-by-mail fulfillment

Catalog order fulfillment

Spare parts distribution

Short-run production with frequent changeovers in any market

Bag Specifications

Film thickness: 1.09 to 4.0 mil

Width: 2" to 12"

Length: 5" to 20"

Pass-Through: 5" (6.7 cm)

Bag Load Capacity: Up to 5 lbs (with load shelf)

Specifications of the Autobag 550

Electrical: 110V to 240V VAC, 50/60 Hz

Power Consumption: 1500 Watts (VA) max

Air: 5 CFM/80 psi of clean, dry air

Dimensions: 37.6"W x 64.5"D x 37.1"-47.1"H (86cm x 104cm x 81-109cm)

Weight: 390 lbs (176 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your bagging equipment.