



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Autobag 600 Bagging System



At a Glance

- Easily integrates with inline printers, counters, scales, and conveyors
- 45 degree tilt option available
- Simple changeover
- Control screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring
- Processor controlled servo motors, Ethernet-capable networking
- Flexible mechanical design streamlines integration
- Simple height adjustment and casters for operator comfort and portability

Buy your [bags-on-a-roll](#) from us, and get a discount on this Autobag bagger!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Wide Bagger Optimizes Reliability, Flexibility and Ergonomics

The Autobag 600 bagger is a technologically-advanced, wide automatic filling and sealing machine designed for reliability, flexibility and optimizing packaging throughput. Capable of cycling at speeds over 65 bags per minute, this system delivers maximum machine uptime while lowering total cost of ownership.

State-of-the-art engineering has led to an innovative, inherently safe design. No light curtains or double palm switches are required to achieve safe hand-load operation. The Autobag 600 is configurable for left- or right-hand access to the HMI, cycle switch and bag loading area, improving ergonomics and operator productivity.

Flexibility has been built into the system, allowing the Autobag 600 to meet the needs of any large packaging operation. The open design makes this bagger highly compatible with Autobag and third-party counters, scales and infeeds. The Autobag 600 can also be networked to facilitate full pack station integration and central monitoring. When integrated with the AutoLabel 600 inline imprinter, a complete Print-and-Pack station is achieved.

A straightforward, simple design with very few moving parts reduces lifetime cost and improves reliability, while on-board diagnostics and modular components simplify maintenance.

When used with genuine [Autobag pre-opened bags-on-a-roll or bags-in-a-box](#), the Autobag 600 ushers in the next evolution of high-quality, reliable and flexible wide bag packaging, backed by the industry's most comprehensive engineering and field service network.

User Benefits

Easily integrates with inline printers, counters, scales, and conveyors for semi- to fully-automatic bagging

Multi-position unwind with tension control simplifies changeover

16" wide bag loading area is ideal for large or bulk products

AutoTouch Control Screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring

Processor controlled servo motors, ethernet-capable networking, and flexible mechanical design streamline integration

Compact footprint minimizes floor space

Simple height adjustment and casters for operator comfort and portability

A 45 degree tilt option is available for orienting long or delicate products

Adjustable pass-through up to 6" for maximum flexibility and packaging efficiency

Newly designed bag sealer area combined with improved temperature control and optional seal-flatteners ensure consistent, high-quality seals

Over 100 styles of stock bags; custom bags include printing in up to 10 colors and a variety of special features

Optional Additions: range of infeed funnels, seal flatteners, raised unwind, SimpleCount counting system, product load tray, bags-in-a-box adapter

Typical Applications

Aerospace & defense

Apparel & accessory packaging

Automotive

Electronics

Hardware & fasteners

Healthcare

Hobby & craft

Household products

Personal products

Pet products

Toys

Bag Specifications

Film thickness: 1.09 to 4.0 mil

Width: 4" to 16"

Length: 5.5" to 27" (36" unsupported)

Pass-Through: 6" (15.24 cm)

Bag Load Capacity: Up to 5 lbs (with load shelf)

Specifications of the Autobag 600

Electrical: 110V to 240V VAC, 50/60 Hz

Power Consumption: 1500 Watts (VA) max

Air: 5 CFM/80 psi of clean, dry air

Dimensions: 41.6"W x 69.5"D x 37.1"-47.1"H (105.6cm x 176.5cm x 94.23-119.6cm)

Weight: 410 lbs (186 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your bagging equipment.