



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Autobag 600 Horizontal Wide Bagging System



At a Glance

- Large load area for order prep and bulk product queuing
- Simple machine design minimizes operator training requirements
- Left or right hand operation
- Flexible mechanical design streamlines integration
- Simple height adjustment and casters for operator comfort and portability

Buy your [bags-on-a-roll](#) from us, and get a discount on this Autobag bagger!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Large Load Area for Order Prep for Large Bag Packaging

The Autobag 600 Horizontal bagger is an automatic filling and sealing machine capable of running 16" wide bags, with a large load area for order prep and bulk product queuing. A compact design minimizes floor space. Developed for reliability, flexibility and optimizing packaging throughput, this system delivers maximum uptime while lowering total package cost.

The Autobag 600 Horizontal bagger boasts many other technologically advanced functions. A multi-position unwind with tension control simplifies changeover. A straightforward, clean layout with very few moving parts reduces lifetime cost and improves reliability, while on-board diagnostics and modular components simplify maintenance. AutoTouch Control Screen accesses help system, on-board diagnostics, and performance data.

When used with genuine [Autobag pre-opened bags-on-a-roll or bags-in-a-box](#), the Autobag 600 Horizontal ushers in the next evolution of high-quality, reliable and flexible wide bag packaging, backed by the industry's most comprehensive engineering and field service network.

User Benefits

24" conveyor boasts a generous open-space design, enabling unrestricted access and effortless transition onto secondary conveyance systems

Simple machine design minimizes operator training requirements - perfect for high-turnover, seasonal labor

Inherently safe design provides maximum operator protection

Load direction configureable for left- or right- hand operation

Multi-position unwind with tension control simplifies changeover
Adjustable pass-through up to 6" for maximum flexibility and packaging efficiency
Advanced sealing technology and temperature control ensure consistent, high-quality seals
Fewer moving parts reduce ownership cost and improve reliability, while on-board diagnostics and modular components simplify maintenance
AutoTouch Control Screen accesses, help system, on-board diagnostics, and performance data

Typical Applications

Apparel and Accessory Packaging
Kitting
PPE and Medical
Appliance Parts

Bag Specifications

Film thickness: 1.09 to 4.0 mil
Width: 4" to 16"
Length: 5.5" to 36"
Pass-Through: 6" (15.24 cm)
Bag Load Capacity: Up to 5 lbs (with load shelf)

Specifications of the Autobag 600 Horizontal

Electrical: 10V to 240V VAC, 50/60 Hz
Power Consumption: 650 Watts (VA) max
Air: 5 CFM/80 psi of clean, dry air
Width: 34.38"W x 66.6"L x 34.15" load table height
Top of HMI: 53.58"
Weight: 570 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your bagging equipment.