



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Autobag 650 Bagging System



At a Glance

- Next-bag-out printing
- 45 degree tilt option available
- 16 inch wide bag loading area is ideal for large or bulk products
- Control screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring
- Processor controlled servo motors, Ethernet-capable networking
- Flexible mechanical design streamlines integration
- Simple height adjustment and casters for operator comfort and portability

Buy your [bags-on-a-roll](#) from us, and get a discount on this Autobag bagger!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Bagger Optimizes Reliability, Flexibility and Ergonomics

The Autobag 650 is a technologically-advanced, wide automatic filling and sealing machine designed for reliability, flexibility and optimizing packaging throughput. Capable of cycling at speeds up to 40 bags per minute, this system delivers maximum machine uptime while lowering total cost of ownership.

Next-bag-out printing is achieved with an advanced thermal transfer imprinter positioned directly over the next large bag to be loaded. This ensures accuracy and efficiency in applications that require frequent product and label changeovers, prevents product queuing and eliminates a separate labeling operation.

State-of-the-art engineering has led to an inherently safe and flexible design. No light curtains or double palm switches are required to achieve safe hand-load operation. The system is configurable for left- or right-hand access to the HMI, cycle switch, and ribbon and bag loading areas, improving ergonomics and operator productivity. Plus, the Autobag 650 can be networked to facilitate full pack station integration and central monitoring. A 45 degree tilt option is available for orienting long or delicate products.

A straightforward, simple design with very few moving parts reduces lifetime cost and improves reliability, while on-board diagnostics and modular components simplify maintenance.

When used with genuine [Autobag pre-opened bags-on-a-roll or bags-in-a-box](#) and AutoLabel Thermal Transfer Ribbon, the Autobag 650 ushers in the next evolution of high-quality, reliable and flexible wide bag packaging, backed by the industry's most comprehensive engineering and field service network.

User Benefits

Next-bag-out printing prevents product queuing and reduces waste

Multi-position unwind with tension control simplifies changeover

AutoTouch Control Screen accesses operator tutorials, help system, on-board diagnostics, and performance monitoring

16" wide bag loading area is ideal for large or bulk products

Newly designed bag sealer area combined with improved temperature control and optional seal-flatteners ensure consistent, high-quality seals

Processor controlled servo motors, ethernet-capable networking, and flexible mechanical design streamline integration

Compact footprint minimizes floor space

Simple height adjustment and casters for operator comfort and portability

A 45 degree tilt option is available for orienting long or delicate products

Adjustable pass-through up to 6" for maximum flexibility and packaging efficiency

Easily integrates with third-party systems for mail order fulfillment applications

Modular components and dedicated service access simplify maintenance and repairs to maximize uptime

Optional Additions: handheld or tabletop bar code scanner, range of infeed funnels, seal flatteners, raised unwind, SimpleCount counting system, bags-in-a-box adapter

Typical Applications

Mail order and ecommerce fulfillment

Prescription-by-mail fulfillment

Catalog order fulfillment

Spare parts distribution

Short-run production with frequent changeovers in any market

Bag Specifications

Film thickness: 1.09 to 4.0 mil

Width: 4" to 16"

Length: 5.5" to 27" (36" unsupported)

Pass-Through: 6" (15.24 cm)

Bag Load Capacity: Up to 5 lbs (with load shelf)

Specifications of the Autobag 650

Electrical: 110V to 240V VAC, 50/60 Hz

Power Consumption: 1500 Watts (VA) max

Air: 5 CFM/80 psi of clean, dry air

Dimensions: 41.6"W x 69.5"D x 37.1"-47.1"H (105.6cm x 176.5cm x 94.23-119.6cm)

Weight: 450 lbs (204 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your bagging equipment.