



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Starview FAB Fully Automatic Blister Sealer



At a Glance

- Complete PLC machine control with color touch screen operator interface
- Blister feeder, card feeder, and finished package unloader standard
- Smooth and reliable table operation with heavy-duty cam indexer and AC variable frequency drive
- Excellent for high volume OEMs and contract packagers
- 4, 6, and 8-station models offered
- Heavy-duty industrial design and construction

Buy your [blisters and cards](#) from us, and get a discount on this Starview blister sealer!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fully Automatic Blister Sealing Up to 18 Cycles per Minute

Starview FAB Series fully automated rotary type blister sealing machines are ideal for high volume or JIT production. Given the proper conditions these machines are capable of up to 18 cycles per minute in production.

The FAB Series automated rotary blister sealing machines are built with the capability to feed blisters, blister cards, and discharge finished packages when proper tooling is installed.

These machines may be used for conventional carded blisters, full face blisters, and half-clamshell styles.

The FAB Series may be equipped with an optional quick-change assembly to reduce changeover times when relieved face plates are utilized. One additional feeder may also be added to the machine to provide reduced labor content when the product is flat and can be fed from a conventional feeder magazine or for producing double card trapped blister packages.

Please [contact Pro Pac](#) or call 888-318-0083 for your blister sealing equipment.

Specifications of FAB Blister Sealers

Specifications	FAB6-1418	FAB6-1824	FAB8-1418
Sealing Area	14" x 18"	18" x 24"	14" x 18"
Open Stations	2	2	4
Blister Feeder	1 Standard	1 Standard	1 Standard
Card Feeder	1 Standard	1 Standard	1 Standard
Finished Pkg Unload	Standard	Standard	Standard
Max Blister Depth	3.5"	3.5"	3.5"
Avg Cycle Speed	1 - 18 CPM	1 - 14 CPM	1 - 18 CPM
Electrical	208-230V / 3Ph / 25Amp	208-230V / 3Ph / 45Amp	208-230V / 3Ph / 25Amp

Specifications	FAB8-1418-3	FAB8-1824	FAB8-1824-3
Sealing Area	14" x 18"	18" x 24"	18" x 24"
Open Stations	3	4	3
Blister Feeder	1 Standard	1 Standard	1 Standard
Card Feeder	2 Standard	1 Standard	2 Standard
Finished Pkg Unload	Standard	Standard	Standard
Max Blister Depth	3.5"	3.5"	3.5"
Avg Cycle Speed	1 - 18 CPM	1 - 16 CPM	1 - 16 CPM
Electrical	208-230V / 3Ph / 25Amp	208-230V / 3Ph / 45Amp	208-230V / 3Ph / 45Amp