



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Starview BSC-II Automatic Carousel Clamshell Sealer

At a Glance

- Designed for high-volume production
- Excellent for large-volume multi-part products
- Standard with 16 stations, more can be manufactured
- Seals plastic to plastic clamshells as well as carded blisters
- Heavy-duty industrial design

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



High-Volume Carousel Clamshell Sealer

Starview BSC II Series carousel type clamshell sealers are designed for high-volume production requirements. The BSC II machines are used for conventional carded blisters, full face blisters, trapped blisters, and half-clamshell styles including applications using Tyvek, foils, and other heat sealable lidstock.

Though 16 station machines are standard, units can be manufactured with 10 to 20 or more stations. Standard sealing areas of 14" x 18" and 18" x 24" are offered, as well as custom sizes.

Standard BSC II machines feature one heated sealing station, one cooling station, one bottom blister feed station, one card feed station, one top blister feed station, one finished package unload station, with the remaining stations used for operator product loading and advanced automation such as printing, vision systems, product detection, etc.

Starview BSC II Series carousel machines may be used for plastic-to-plastic clamshell sealing, conventional carded blisters, trapped blister packages, club-style trapped blister packages, full-face blisters, half-clamshell styles, and applications using Tyvek, foils, and other heat-sealable lidstock.

Features of the Starview BSC II Clamshell Sealer

A wide range of standard and custom automation features available to match your requirements.

ANSI Class 4 machine safety for operation protection.

Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99

databases an on-screen data tracking.

Starview exclusive remote access via standard Ethernet hardware or optional Wi-Fi router gives management access to real-time process information from the machine.

Starview's exclusive hot / cold sealing press system allows plastic-to-plastic sealing of PVC, RPVC, PETG, RPETG, GAG PET, GRG PET, and similar materials without the use of RF generators.

AC Variable frequency precision cam index conveyor drive for smooth table operation and position repeatability.

Automatic card feeder, front and back clamshell feeders, and finished package unloader are standard for high-volume clamshell packaging and reduced labor requirements.

Industry-leading design, construction, features, and customer support.

Please [contact Pro Pac](#) or call 888-318-0083 for your clamshell sealing equipment.

Specifications of BSC II Clamshell Sealers

Specifications	BSC II 16-1418	BSC II 16-1824
Nominal Sealing Area	14" x 18"	18" x 24"
Sealing Fixtures	16	16
Clamshell Front Feeder	Standard	Standard
Clamshell Back Feeder	Standard	Standard
Card Feeder	Standard	Standard
Finished Package Unloader	Standard	Standard
Max Clamshell / Blister Depth	3.0"	3.0"
Max Clamshell Back Height	2.5"	2.5"
Ave Cycle Speed Clamshell	1 - 14 CPM	1 - 12 CPM
Ave Cycle Speed Blister	1 - 18 CPM	1 - 14 CPM
Electrical	208-230 Volts / 3 Phase / 35 Amps	208-230 Volts / 3 Phase / 50 Amps

Please [contact Pro Pac](#) or call 888-318-0083 for your clamshell sealing equipment.