



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# PHS6 Semi-Automatic 6-Station Clamshell Sealer



## At a Glance

- Designed for medium to high volume production
- Available with 3, 6, and 8 stations
- Seals plastic to plastic clamshells as well as carded blisters
- Heavy-duty industrial design

Buy your [clamshells](#) from us, and get a discount on this Starview clamshell sealer!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## 6-Station Clamshell Sealing for More Packages per Station

Starview PHS Series semi-automatic rotary type clamshell and blister sealers are designed for medium to higher volume production requirements.

These machines may be used for plastic-to-plastic clamshell sealing as well as conventional carded blisters, full face blisters and half-clamshell styles including applications using Tyvek, foils, and other heat sealable lidstock.

The PHS Series units are available in 3, 6, and 8 station designs. The standard machines feature one heated sealing station and one cooled station.

Starview's PHS Series rotary heat sealers are designed to include an optional automatic card feeding system and automatic package discharge system on most models. These may be self-standing or permanently attached depending on the model. An optional chiller installed in the machine eliminates the need for routing in-plant chilled water to the machine. Casters and a lightweight package hold down system are also offered for greater versatility.

## Features of the PHS Series

Hot/Cold process provides safe and efficient sealing of PVC, PETG, GAG PET & similar materials

Complete PLC machine control with touch screen operator interface

Optional finished package unloader available

Smooth and reliable table operation with heavy-duty cam indexer and AC variable frequency drive

Excellent for high volume OEM's and contract packagers

Heavy-duty industrial design floor model machine

Please [contact Pro Pac](#) or call 888-318-0083 for your clamshell sealing equipment.

## Specifications of PHS Clamshell Sealers

Specifications	PHS3-1418	PHS6-1418	PHS6-1824
Max Sealing Area	14" x 18"	14" x 18"	18" x 24"
Open Loading Stations	1	4	4
Card Feeder	N/A	N/A	N/A
Finished Package Unloader	N/A	Optional Self-Standing	Optional Attached
Max Clamshell/Blister Depth	3.25"	3.25"	3.25"
Max Clamshell Back Height	1.25"	1.5"	3.0"
Clamshell Cycle Speed	1 - 6 CPM	1 - 12 CPM	1 - 12 CPM
Blister Cycle Speed	1 - 8 CPM	1 - 15 CPM	1 - 15 CPM
Approximate Size	55"W x 50"D x 70"H	66"W x 70"D x 70"H	88"W x 105"D x 90"H
Approximate Weight	1,500 LB	2,200 LB	2,900 LB

Specifications	PHS8-1418	PHS8-1824
Max Sealing Area	14" x 18"	18" x 24"
Open Loading Stations	6	6
Card Feeder	Optional Self-Standing	Optional Attached
Finished Package Unloader	Standard	Standard
Max Clamshell/Blister Depth	3.25"	3.25"
Max Clamshell Back Height	1.5"	3.0"
Clamshell Cycle Speed	1 - 12 CPM	1 - 10 CPM
Blister Cycle Speed	1 - 15 CPM	1 - 14 CPM
Approximate Size	96"W x 90"D x 70"H	120"W x 115"D x 90"H
Approximate Weight	3,500 lbs	4,300 lbs