



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Adco 16B Tri-Seal Carton Closer

At a Glance

- Positive, continuous motion lugged carton transfer design
- Speeds up to 80 cycles per minute
- Fast, easy changeover
- Stainless steel construction

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Closing Tri-Seal Cartons at Speeds Up to 80 per Minute

Featuring positive, continuous-motion lugged carton transfer design, the new Adco 16B is the right answer for your tri-seal carton closing needs. When it comes to speed, flexibility, footprint and value, the 16B hits the mark.

Designed to seal a wide variety of carton shapes and sizes, the affordable 16B accepts cartons back-to-back at speeds up to 80 cycles per minute.

No complex positioning systems required. Adco's time-tested lugged transfer design keeps positive control of the carton all the way through the closing and sealing operation. This reliable and simple-to-operate tri-seal carton closer is ideal for the most demanding and cost-conscious production environments.

Like all Adco machines, the 16B is constructed in stainless steel and is available in both standard and washdown configurations.

Benefits

Stainless steel construction improves cleanability and eliminates corrosion

Positive, continuous motion lugged carton transfer maximizes control and reliability

Fast, easy changeover improves productivity and reduces downtime

Large carton size range protects your investment as products change

Advanced guard design keeps operators safe and maximizes maintenance access

Features

- Stainless steel construction
- Compact frame with leveling feet and casters
- Lugged carton transfer system
- Cover left/right orientation
- 1-HP variable speed drive system
- Overhead tucking system
- Powered discharge side belts
- Nordson ProBlue hot melt glue system
- Allen-Bradley control package
- Category 3 safety system with a fully-interlocked barrier guard package
- Many options available upon request

Options

- Transfer left or right orientations available
- Cover supply on left or right
- Washdown construction
- Economy glue flaps
- Downstream back-up detection
- Marking and coding systems
- PLC & HMI upgrades
- Integrate with an Adco or 3rd party supplied upstream product loading system
- Integrate with an Adco supplied upstream carton former

Applications

- Baked goods
- Flow-wrapped products
- Dairy products
- Snack foods
- Consumer products

Carton Size Range

- Length of Opening: 4" to 12" (101 to 305mm)
- Width of Opening: 4" to 10" (101 to 254mm)
- Carton Depth: 1" to 4" (25 to 101mm)

Specifications

- Electrical: 230 VAC, 3-Phase with ground (PE), 60 Hz, 30A
- Air: 2 CFM @ 70 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.