



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Adco 18TS Inline Top-Seal Carton Closer



At a Glance

- Positive, continuous motion lugged carton transfer design
- Speeds up to 80 cycles per minute
- Fast, easy changeover
- Stainless steel construction

Buy your cartons from us, and get a discount on this Adco carton closer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Closing RSC and Tablock Tuck Cartons at Speeds Up to 60 per Minute

Featuring positive, continuous-motion lugged carton transfer design, the Adco 18TS is a perfect solution for inline sealing of single flap top load, RSC, and tablock tuck cartons. With its simple design and ability to handle wide variety of carton shapes and sizes at variable speeds up to 60 cartons per minute, the versatile 18TS is packed with value.

Cartons arrive back-to-back and are indexed into the 18TS by either an air-actuated push-off indexer or a dual-lugged mechanical indexer. Adco's lugged transfer design maintains control of the carton all the way through the closing and sealing operation. This reliable and simple to operate carton closer is ideal for the most demanding and cost conscious production environments.

Like all ADCO machines, the 18TS is available in both standard and washdown configurations.

Benefits

- Stainless steel construction improves cleanability and eliminates corrosion
- Positive, continuous motion lugged carton transfer maximizes control and reliability
- Lugged overhead chain design maximizes carton squaring and product quality
- Fast, easy changeover improves productivity and reduces downtime
- Large carton size and style range with protects your investment as products change
- Advanced guard design keeps operators safe and maximizes maintenance access

Features

Stainless steel construction

Air-actuated push-off indexer or mechanical dual-lugged indexer
Lugged carton transfer system
Powered side compression/discharge belts
Variable speed drive system
Dust flap tucking system
Powered discharge side belts
Compact frame with leveling feet and casters
Nordson ProBlue hot melt glue system (when glue is specified)
Allen-Bradley control package
Fully-interlocked barrier guard package
Many options available upon request

Options

Washdown construction
Tuck or glue style cartons
Downstream back-up detection
Open major flap detect

Applications

Flow-wrapped products
Frozen foods
Snack foods
Baked goods
Household products

Carton Size Range

Length of Opening: 4" to 12" (102 to 305mm)
Width of Opening: 4" to 10" (102 to 254mm)
Carton Depth: 1.5" to 6" (40 to 160mm)

Specifications

Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 30A
Air: 2-3 CFM @ 65-70 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.