

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

Contact

Our Packaging Experts solutions@propac.com

Adco RAC-120 Compact Right-Angle Carton Closer



At a Glance

- Positive, continuous motion lugless carton transfer design
- Speeds up to 120 cartons per minute
- Fast, no-tool changeover
- Stainless steel construction

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

High-Speed Tri-Seal Carton Closer at Speeds Up to 120 per Minute

Featuring flexible design and a compact footprint, the Adco RAC-120 high speed tri-seal carton closer was designed with your needs in mind.

With its precision servo-powered 90-degree transfer, the RAC-120 can seal a wide variety of carton shapes and sizes at speeds up to 120 cycles per minute.

Adco's time-tested lugged carton transfer system with powered overhead and flexible grippers maintain positive control of the carton all the way through the closing and sealing operation. This reliable and simple to operate tri-seal carton closer is ideal for the most demanding production environments.

Like all Adco machines, the RAC-120 is constructed in stainless steel and is available in both standard and washdown configurations.

Benefits

Stainless steel construction improves cleanability and eliminates corrosion
Vacuum infeed meters cartons into the machine and helps square cartons before closing
Positive, on-demand lugged carton transfer maximizes control and reliability
Overhead belt and flexible gripper design improves oversize carton handling
Swing away overhead conveyors to quickly clear jams

Fast, no-tool changeover improves productivity and reduces downtime Large carton size range protects your investment as products change Advanced guard design keeps operators safe and maximizes maintenance access

Features

Stainless steel construction

Speeds up to 120 cartons per minute

Accepts cartons randomly or back-to-back

Servo-driven on demand 90-degree transfer system

Compact 8.5' frame with leveling feet and casters

Lugged carton transfer system

Nordson ProBlue FLEX hot melt glue system

Allen-Bradley PLC control package with touch screen HMI

Category 3 safety system with a fully-interlocked barrier guard package

Many options available upon request

Options

Washdown construction

Transfer left or right orientations available

Cover supply on left or right

Downstream back-up detection

Open flap detect & reject system

Marking and coding systems

PLC & HMI upgrades

Integrate with an Adco or 3rd party supplied upstream product loading system

Integrate with an Adco supplied upstream carton former

Applications

Snack foods

Ice cream novelties

Flow-wrapped products

Frozen foods

Ready meals

Dairy products

Baked good

Carton Size Range

Length: 4" to 14" (101 to 355mm) Width: 3" to 12" (75 to 305mm) Depth: 1" to 5" (25 to 125mm)

Specifications

Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 30A

Air: 2 CFM @ 70 psi

Please contact Pro Pac or call 888-318-0083 for your cartoning equipment.