



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Adco RAC-120 Compact Right-Angle Carton Closer



At a Glance

- Positive, continuous motion lugged carton transfer design
- Speeds up to 120 cycles per minute
- Fast, easy changeover
- Stainless steel construction

Buy your cartons from us, and get a discount on this Adco carton closer!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

High-Speed Tri-Seal Carton Closer at Speeds Up to 120 per Minute

Featuring flexible design and a compact footprint, the Adco RAC-120 high speed tri-seal carton closer was designed with your needs in mind. With its precision servo-powered 90-degree transfer, the RAC-120 can seal a wide variety of carton shapes and sizes at speeds up to 120 cycles per minute.

Adco's time-tested lugged carton transfer system with powered overhead and flexible grippers maintain positive control of the carton all the way through the closing and sealing operation. This reliable and simple to operate tri-seal carton closer is ideal for the most demanding production environments.

Like all Adco machines, the RAC-120 is constructed in stainless steel and is available in both standard and washdown configurations.

Benefits

- Stainless steel construction improves cleanability and eliminates corrosion
- Positive, continuous motion lugged carton transfer maximizes control and reliability
- Fast, no-tool changeover improves productivity and reduces downtime
- Large carton size range protects your investment as products change
- Advanced guard design keeps operators safe and maximizes maintenance access

Features

Stainless steel construction

Speeds up to 120 cartons per minute
Accepts cartons randomly or back-to-back
Servo-driven 90-degree transfer system
Compact 8.5' frame with leveling feet and casters
Lugged carton transfer system
Nordson ProBlue hot melt glue system
Allen-Bradley PLC control package
Category 3 safety system with a fully-interlocked barrier guard package
Many options available upon request

Options

Economy glue flaps
Downstream back-up detection
Open major flap detect

Applications

Snack foods
Flow-wrapped products
Frozen foods
Ready meals
Dairy products
Baked good

Carton Size Range

Length: 4" to 14" (102 to 355mm)
Width: 3" to 12" (75 to 305mm)
Depth: 1" to 5" (25 to 125mm)

Specifications

Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 30A
Air: 10 CFM @ 70 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.