

**Professional Packaging Systems** 

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

#### Contact

Our Packaging Experts solutions@propac.com 888-318-0083

# Adco SLC High-Speed Inline Carton Closer



#### At a Glance

- Variable-speed drive system, precision servocontrolled turning chains
- Speeds up to 200 cycles per minute
- Large carton size and style range
- Stainless steel construction

#### Pricing

#### Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

#### Closing a Variety of Tri-Seal Cartons at Speeds Up to 200 per Minute!

The compact, Adco SLC high-speed inline tri-seal carton closer is designed to handle wide variety of carton shapes and sizes at speeds up to 200 cartons per minute. The versatile lugless inline SLC carton closer gets the job done, fast!

Featuring a variable-speed drive system, precision servo-controlled turning chains and no-tool changeover, the SLC packs a lot of features into its small frame.

The Adco SLC overhead belt and flexible gripper design easily handles bulging and oversize cartons. This reliable and simple to operate carton closer is ideal for the most demanding and cost-conscious production environments.

Like all Adco machines, the SLC is available in both standard and washdown configurations.

### **Benefits**

Stainless steel construction improves cleanability and eliminates corrosion Vacuum infeed meters cartons into the machine and helps square cartons before closing Positive, on-demand lugged carton transfer maximizes control and reliability Overhead belt and flexible gripper design improves oversize carton handling Swing away overhead conveyors to quickly clear jams Fast and easy no-tool changeover improves productivity and reduces downtime Large carton size and style range which protects your investment as products change Advanced guard design keeps operators safe and maximizes maintenance access

#### Features

Stainless steel construction 90 degree carton turn section with on-demand servo controlled turning chains Cover right or cover left orientation No-tool changeover with digital readouts Variable speed drive system Accepts cartons randomly or back-to-back Compact frame with leveling feet and casters Nordson ProBlue FLEX hot melt glue system Allen-Bradley PLC control package with touch screen HMI Category 3 safety system with fully-interlocked barrier guard package Many options available upon request

### Options

Washdown construction Transfer Counter-clockwise or clockwise orientations available Cover supply on left or right Downstream back-up detection Open flap detect & reject system Marking and coding systems PLC & HMI upgrades Integrate with an Adco or 3rd party supplied upstream product loading system Integrate with an Adco supplied upstream carton former

## Applications

Snack foods Flow-wrapped products Frozen foods Ready meals Dairy products Baked goods

### **Carton Size Range**

Length of Opening: 4" to 11.75" (101 to 300mm) Width of Opening: 3" to 11.75" (75 to 300mm) Carton Depth: 1" to 5" (25 to 125mm)

### **Specifications**

Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 30A Air: 2 CFM @ 70 psi

Please contact Pro Pac or call 888-318-0083 for your cartoning equipment.