



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Adco ZTC-30 Tri-Seal Carton Closer



## At a Glance

- Built-in metering system to ensure proper spacing between packages
- Speeds up to 30 cycles per minute
- For sealing oversize club store style tri-seal cartons
- Stainless steel construction

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Closing Tri-Seal Cartons at Speeds Up to 80 per Minute

Designed to provide maximum carton closing performance and reliability at an affordable price, the compact Adco ZTC-30 Tri-Seal Carton Closer is ideal for the most demanding and cost-conscious production environments.

Designed to close oversize tri-seal cartons at speeds up to 30 cartons per minute, the ZTC-30 features a three foot infeed conveyor with a built-in metering system to ensure proper spacing between packages as they enter the machine. A reliable walking beam indexing system, with optional servo-control, pushes each package into the sealing area where glue is applied to the sidewalls and the cover is plowed. The package is then pushed onto a lugged conveyor where the front flap is glued and sealed.

Like all Adco machines, the ZTC-30 features stainless steel construction and is available in either standard or washdown configurations.

## Benefits

- Optimized for sealing 'oversize' club store style tri-seal cartons
- Durable yet economical design for low-speed sealing applications saves money
- Stainless steel construction improves cleanability and eliminates corrosion
- Fast, easy changeover reduces downtime and improves productivity
- Compact footprint saves space and eases integration into tight areas

## Features

- 3' long low-friction infeed conveyor

Air actuated carton metering system  
90-degree lugged transfer for front flap sealing  
Compact footprint  
2-station walking beam indexing system with servo drive  
Air actuated side flap sealing system  
Allen-Bradley PLC control package with touch screen HMI interface  
Category 3 safety system with fully-interlocked barrier guard package

## Options

Washdown construction  
Transfer/Cover left or right orientations available  
Downstream back-up detection  
Open flap detect  
Marking and coding systems  
PLC & HMI upgrades  
Integrate with an Adco or 3rd party supplied upstream product loading system  
Integrate with an Adco supplied upstream carton former

## Applications

Snack foods  
Baked goods in trays  
Flow-wrapped products  
Frozen meats  
Dairy  
Personal care  
Cosmetics

## Carton Size Range

Length of Opening: 4" to 12" (101 to 305mm)  
Width of Opening: 4" to 10" (101 to 254mm)  
Carton Depth: 1" to 4" (25 to 101mm)

## Specifications

Electrical: 230 VAC, 20A  
Air: 5 CFM @ 80 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.