



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Adco 15DZ Hand Load Carton Former



At a Glance

- Forms a wide range of carton sizes and styles
- Speeds up to 60 cycles per minute
- Special horizontal flap tucker for difficult bag-in-box applications
- Innovative twist rotary carton feeder

Buy your [cartons](#) from us, and get a discount on this Adco carton former!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact and Economical, Forming Up to 60 Cartons per Minute

Featuring a smooth and efficient single-head rotary carton feed system, the Adco 15DZ delivers class-leading carton erecting performance in a compact and economical package.

Capable of forming a wide range of tray sizes and styles at speeds up to 60 cycles per minute, the affordable 15DZ is ideal for the most demanding and cost conscious production environments.

Fast changeover, simple operation, ergonomic design and the optional ability to switch between intermittent or continuous motion mode really set this machine apart from other cartoners.

If you have a challenging bag-in-box application, you'll love the special flap tucker design of the 15DZ. Like all ADCO machines, the 15DZ is constructed in stainless steel and is available in both standard and washdown configurations.

Benefits

Stainless steel construction provides maximum strength as well as improved sanitation over traditional designs

Fast, easy changeover with scales and pointers and available digital counters maximizes reliability and increases productivity

Intuitive and modern interface enhances operator experience and improves overall equipment effectiveness (OEE)

Advanced guard design keeps operators safe and maximizes maintenance access

Features

Stainless steel construction

Compact frame with leveling feet and casters
Double-head rotary carton feeder with optional orbital feeder and pre-break
Ergonomically-designed product load table
Capable of sealing either tuck-lock style or glued cartons
Nordson ProBlue hot melt glue system (when glue is specified)
Allen-Bradley control package
Category 3 safety system with a fully-interlocked barrier guard package
Many options available upon request

Options

Washdown construction
Glue or tuck style cartons
Marking and coding systems
10' bolt on infeed conveyor
Powered hopper
Switchable intermittent to continuous motion feed

Applications

Flow-wrapped products
Frozen foods
Bag-in-box
Baked goods
Snack foods
Dairy products

Carton Size Range

Length of Opening: 1" to 9" (25 to 229mm)
Width of Opening: 1" to 4" (25 to 102mm)
Carton Depth: 4" to 12" (100 to 305mm)

Specifications

Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 30A
Air: 10 CFM @ 95 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.