



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Adco 15HCS Horizontal End Load Carton Sealer

At a Glance

- Forms a wide range of carton sizes and styles
- Speeds up to 50 cycles per minute
- Continuous motion lugged carton transfer system
- Fast, easy changeover improves productivity and reduces downtime

Buy your [cartons](#) from us, and get a discount on this Adco carton former!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Compact and Economical, Forming Up to 50 Cartons per Minute

The affordable ADCO 15HCS horizontal carton sealer is perfect for new product launch or short production runs. This compact and easy-to-operate continuous motion machine is capable of sealing a wide range of carton sizes at speeds up to 50 cartons per minute.

Simply place a pre-filled carton into the 15HCS from either side of the load area and it will take care of the rest; quick, easy and efficient.

Designed with flexibility and portability in mind, the robust 15HCS horizontal carton sealer is ideal for the most demanding and cost conscious production environments. Like all ADCO machines, the 15HCS is constructed in stainless steel and is available in both, standard and washdown configurations.

Benefits

- Stainless steel construction improves cleanability and eliminates corrosion
- Positive, continuous motion lugged carton transfer maximizes control and reliability
- Fast, easy changeover improves productivity and reduces downtime
- Large carton size range protects your investment as products change
- Pressurized glue system minimizes glue consumption and reduces clean up
- Advanced guard design keeps operators safe and maximizes maintenance access

Features

- Stainless steel construction
- Continuous motion lugged carton transfer system

- Compact frame
- Easy access drive system
- Quick adjust
- Casters and leveling feet
- Nordson ProBlue hot melt glue system
- Simple relay logic controls
- Fully-interlocked barrier guard package
- Many options available upon request

Options

- Powered discharge side belts
- Washdown construction
- Tuck or glue style cartons
- Marking and coding systems
- 10' bolt on conveyor
- Powered hopper

Applications

- Flow-wrapped products
- Baked goods
- Snack foods
- Frozen foods
- Consumer products
- Confectionery

Carton Size Range

- Length of Opening: 2" to 12" (12 to 305mm)
- Width of Opening: .75" to 4.5" (20 to 115mm)
- Carton Depth: 3.5" to 12" (90 to 305mm)

Specifications

- Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 25A
- Air: 10 CFM @ 95 psi

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.