

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

Contact

Our Packaging Experts solutions@propac.com 888-318-0083

Adco JET-60 Hand Load Carton Former



At a Glance

- Utilizes a smooth and efficient double-head rotary carton feed system
- Stainless steel construction
- Fast changeover, simple operation and ergonomic design
- Speeds up to 60 cycles per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Compact and Economical, Seals a Wide Range of Cartons

Featuring a smooth and efficient double-head rotary carton feed system with optional orbital feed and pre-break, the Adco JET-60 delivers class-leading carton erecting performance in a compact and economical package.

Capable of erecting and sealing a wide range of carton sizes at speeds up to 60 cycles per minute, the JET-60 is ideal for the most demanding and cost conscious production environments.

Fast changeover, simple operation and ergonomic design, along with the ability to easily add a barrel cam auto-load system, make this cartoner unique.

The special flap tucker design of the JET-60 meets the demand of challenging applications.

Like all Adco machines, the JET-60 is constructed in stainless steel and is available in standard or washdown configurations.

Benefits

Stainless steel construction improves cleanability and reduces corrosion

Rotary carton feeder ensures smooth, efficient operation

Optional orbital carton feeder with vacuum pre-break will open the most challenging cartons

Special horizontal flap tucker takes the challenge out of difficult bag-in-box applications

Large carton size range protects your investment as products change

Advanced guard design keeps operators safe and maximizes maintenance access

Optional barrel cam auto-load conversion kit makes it easy and affordable to convert from manual to

Features

Stainless steel construction, welded frame

Compact frame with leveling feet and casters

Double-head rotary carton feeder with ergonomically-designed product load table

Ergonomically-designed product load table

Capable of closing either tablock style or glued cartons

Nordson ProBlue hot melt glue system (when glue is specified)

Allen-Bradley control package

Category 3 safety system with a fully-interlocked barrier guard package

Optional barrel cam auto-load conversion kit

Many options available upon request

Options

Available auto-load barrel cam conversion

Orbital feeder with pre-break

Washdown construction

Glue or tablock tuck style closure

Marking and coding systems

10' bolt on infeed conveyor

Powered magazine

Switchable intermittent to continuous motion feed

Powered side discharge belts

Applications

Flow-wrapped products

Frozen foods

Bag-in-box

Baked goods

Snack foods

Dairy products

Carton Size Range

Length of Opening: 1" to 9" (25 to 229mm) Width of Opening: 1" to 4" (25 to 102mm) Carton Depth: 4" to 12" (100 to 305mm)

Specifications

Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 30A

Air: 10 CFM @ 95 psi

Please contact Pro Pac or call 888-318-0083 for your cartoning equipment.