



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Adco WAE Wrap Around Sleever



At a Glance

- Wrap around sleever perfect for low-speed sleeving operations
- Compact frame
- Easy-to-load inclined magazine
- Stainless steel construction

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Low Speed Sleever Wraps Trays, Tubs, and Multi-Count Products

The innovative and affordable Adco WAE wrap around sleever perfect for sleeving operations with speeds up to 60 sleeves per minute.

The continuous motion WAE features a compact frame, an easy-to-load inclined magazine, and a smooth reciprocating sleeve feeder.

The Adco WAE can be optionally equipped to feed single count trays or tubs automatically, or it can be configured with an optional flighted infeed conveyor system for hand loading of multi-count products. The WAE may also be specified to run either tablock style sleeves or glued sleeves.

The high-speed Adco WAE-90 version comes equipped with servo powered timing screws, 4' horizontal magazine, and 2-head rotary feeder to offer speeds up to 90 sleeves/minute

Like all Adco machines, the WAE is constructed in stainless steel and is available in both standard and various washdown configurations.

Benefits

- Stainless steel construction improves cleanability and eliminates corrosion
- Overhead conveyor with bottom squaring chain ensures proper sealing
- Flexible and adaptable design protects your investment as products change
- Easy to load magazine reduces operator fatigue and increases run time

Advanced guard design keeps operators safe and maximizes maintenance access

Features

- Stainless steel construction
- Compact 9' frame with leveling feet and casters
- Easy to load, inclined sleeve magazine
- Overhead conveyor
- Bottom squaring chain
- Powered takeaway belts
- Capable of forming lock style or glued sleeves
- Nordson ProBlue hot melt glue system (when glue is specified)
- Allen-Bradley PLC control system with touch screen HMI
- Category 3 safety system with a fully-interlocked barrier guard package
- Many options available upon request

Options

- Washdown construction
- Nordson MOD melt on demand hotmelt glue system
- Downstream back-up detection
- Marking and coding systems
- PLC & HMI upgrades

Applications

- Frozen entrees
- Single pack cups, trays and bowls
- Multi-packs of yogurt
- Ready meals
- Consumer products

Carton Size Range

- Length of Opening: 3" to 10" (75 to 250mm)
- Width of Opening: 3" to 9" (75 to 225mm)
- Depth of Carton: 1" to 4" (25 to 101mm)

Specifications

- Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 30A
- Air: 10 CFM @ 95 PSI

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.