



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Adco WSU-HL Wrap Up Hand Load Sleever



At a Glance

- Capable of speeds up to 100 sleeves per minute
- Compact, 14 foot frame with leveling feet and casters
- Ergonomic 72 inch long hand load table
- Positive flap control chains in the closing area
- Stainless steel construction

Buy your [cartons](#) from us, and get a discount on this Adco carton former!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Economical Hand Load Wrap Up Sleever for Multi-Piece Slewing

For speeds up to 100 sleeves/minute, the Adco WSU-HL features a compact frame, an easy-to-load inclined magazine, and a smooth 2-head rotary sleeve feeder.

The continuous motion WSU-HL is designed and configured to run multi-count products that are too complicated to automate with a conventional sleever.

Like all ADCO machines, the WSU-HL is constructed in stainless steel and is available in both standard and various washdown configurations.

Benefits

Stainless steel construction improves cleanability and eliminates corrosion

Ergonomic 72" long hand load table

Flexible and adaptable design protects your investment as products change

Easy to load magazine reduces operator fatigue and increases run time

Advanced guard design keeps operators safe and maximizes maintenance access

Features

Stainless steel construction

Compact, 14' frame with leveling feet and casters

Easy to load, inclined sleeve magazine

Positive flap control chains in the closing area

Powered takeaway belts

Nordson ProBlue FLEX hot melt glue system

Allen-Bradley PLC control system
Category 3 safety system with a fully-interlocked barrier guard package
Many options available upon request

Options

Washdown construction
Horizontal powered magazine
Extended hand load area is available
Automate with an Adco robotic product loading system
Nordson MOD melt on demand hotmelt glue system
Downstream back-up detection
Marking and coding systems
PLC & HMI upgrades

Applications

Frozen entrees
Dairy
Beverage
Baked goods

Carton Size Range

Length of Opening: 4.0" to 9.5" (101 to 240mm)
Width of Opening: 3.0" to 9" (75 to 203mm)
Depth of Carton: 1.0" to 4.0" (25 to 101mm)

Specifications

Electrical: 230/460 VAC, 3-Phase with ground (PE), 60 Hz, 30A
Air: 10 CFM @ 95 PSI

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.