



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Econoseal E-System 2000 Horizontal Cartoner



## At a Glance

- Forms, loads, and closes end load cartons
- Accommodates glue sealing, tuck closure, or hot air closure
- Up to 25 cartons per minute
- Sanitary construction (essentially stainless steel)

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Form, Load, Seal Cartons Up to 25 per Minute

The E-System 2000 automatic horizontal cartoner forms, loads, and closes end-load cartons.

## Operation

1. End-load carton is removed from a supply magazine via vacuum system.
2. Carton is erected at a single product load station.
3. Product is manually or automatically (optional) horizontally loaded into carton.
4. Loaded carton is transported to the closing position for tuck closure or sealing with either hot melt glue or hot air.
5. A completed carton is then automatically delivered from the machine to a convenient working height.

## Features

Up to 25 cartons per minute  
Sanitary construction (essentially stainless steel)  
Intermittent motion  
Up to 25 cartons per minute (depending on carton style and other factors)  
PLC controls  
Compact 78" x 32" (1980 x 813mm)  
Accommodates glue sealing, tuck closure, or hot air closure  
Paperboard or corrugated material  
Left hand or right hand load and discharge

## Options

Extended or reduced sized cartons outside the standard range

Adjustable magazine

Straight back delivery chute

3 light beacon

5' extended carton magazine

Ink print or deboss coding

Pneumatic, overhead pivoting, or tamp style product infeed

Continuous or intermittent motion belt conveyor

Intermittent motion bucket conveyor

CE guarding

## Carton Size Range

Min: 1" x .75" x 4" (25 x 19 x 101mm)

Max: 12" x 4" x 12" (305 x 101 x 305mm)

## Specifications

Electrical: 220 volts, 50/60 Hz, Single phase

Air: 80 psi (6,6 bar) Volume consumption approximately 3.2 cfm, 15.8 SCFM (30 Liters/min)

Weight: Normally less than 1300 lbs (590 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.