



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Econoseal Econo-60 Horizontal Cartoner

## At a Glance

- Forms, loads, and closes end-load cartons
- Accommodates glue sealing, tuck closure, or hot air closure
- Up to 60 cartons per minute
- Sanitary construction (essentially stainless steel)



Buy your [cartons](#) from us, and get a discount on this Econoseal carton former!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Form, Load, Seal Cartons Up to 60 per Minute

The Econoseal Econo-60 manual-load, continuous-motion horizontal cartoner forms and closes end-load cartons at speeds of around 60 cartons per minute.

## Operation

1. End load carton is removed from a supply magazine via a rotary vacuum system.
2. Carton is erected and placed down on continuous moving chain system.
3. Product is manually horizontally loaded into a carton by an operator. Product can be transported to loading area via a product feeding belt conveyor.
4. Loaded carton is transported through the machine and is either tucked closed or applied with hot melt glue and compressed shut.
5. Completed cartons are then automatically delivered from the back of the machine at a convenient working height.

## Features

Sanitary construction (essentially stainless steel)  
Continuous-motion variable speed  
Speeds of 60 cartons per minute  
Accommodates glue sealing or tuck style closure  
Left hand load  
Straight back discharge

## Options

Extended or reduced sized cartons outside the standard range

Adjustable magazine  
3 light beacon  
5' extended carton magazine  
Product feeding belt  
Ink print or deboss coding  
CE guarding

## Carton Size Range

Min: 1" x .75" x 4" (25 x 19 x 102mm)

Max: 8" x 3" x 12" (203 x 76 x 305mm)

## Specifications

Electrical: 220 volts, 50/60 Hz, Single phase

Air: 80 psi (5.5 bar), volume consumption approximately .5 CFM 3 SCFM (12 Liters/min)

Weight: Approximately 2,400 lbs (1,100 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.