



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Econoseal Twinseal Horizontal Cartoner



## At a Glance

- Mechanical, horizontal cartoner seals end load cartons
- Up to 30 cartons per minute
- Accommodates glue sealing or hot air closure
- Sanitary construction (essentially stainless steel)

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Very Popular Semi-Auto Carton Sealer

The Econoseal Twinseal horizontal cartoner utilizes hot melt glue or hot air seal methods. The hot melt glue system is the most popular Twinseal sealing method which minimizes flap compression time and works well with many different board materials and coatings. Alternatively, hot air guns can be used to seal cartons that have either pre-applied adhesive or double sided sealable coatings on the carton board.

## Operation

1. Operator places loaded carton into the machine with inner flaps closed, and presses dual button start.
2. Glue is automatically applied to underside of carton flap(s).
3. Carton is elevated into vertical squaring/compression chamber.
4. Completed, sealed cartons are automatically removed by the delivery chute accessory.

## Features

Sanitary construction (essentially stainless steel).

Up to 30 cartons per minute.

Hand crank lateral adjustment for fast, easy changeover.

Automatic cycle.

Left hand, right hand or straight back delivery chute discharge.

Accommodates glue sealing or hot air closure for paperboard or corrugated cartons.

## Options

Extended or reduced sized cartons outside the standard range

Deboss, ink or hot leaf coding system  
Automated infeed system  
Ability to go 2-up to seal 2 cartons at once for increased output  
Adjustable infeed plow assembly  
Floor stand  
CE guarding

## Carton Size Range

Min: .75" x .75" x 3" (19 x 19 x 76mm)  
Max: 12" x 4" x 12" (305 x 102 x 305mm)

## Specifications

Electrical: 220 volts, 50/60 Hz, Single phase, 1400 watt hot melt system  
Air: 60 psi (4 bar), volume consumption approximately 3.2 CFM 15.8 SCFM (30 Liters/min)  
Weight: Normally less than 300 lbs (136 kg)

Please [contact Pro Pac](#) or call 888-318-0083 for your cartoning equipment.