



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Adco CTF 470V Corrugated Tray Former



At a Glance

- Speeds up to 70 cycles per minute
- Stainless steel construction
- Fast, no-tool changeover
- Easy to load high capacity magazine

Buy your trays from us, and get a discount on this Adco tray former!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Fast, Heavy-Duty, Tray Former Delivers Up to 70 Tray per Minute

Capable of forming a wide range of sizes and styles of corrugate trays, the ergonomically designed Adco CTF 470V delivers class-leading performance at speeds up to 70 cycles per minute.

Featuring a 5' powered magazine and fast no-tool changeover, the compact and simple-to-operate CTF 470V is ideal for the most demanding production environments.

Like all Adco machines, the CTF 470V is constructed in stainless steel and is available in both standard and washdown configurations.

Benefits

Compact footprint saves space and simplifies integration

Flexible design makes tray size and style changes easier and less costly

Fast, no-tool changeover improves productivity and reduces downtime

Stainless steel construction improves cleanability and eliminates corrosion

Easy to load high capacity magazine reduces operator fatigue and increases run time

Advanced guard design keeps operators safe and maximizes maintenance access

Features

Stainless steel construction

Servo-controlled forming section

Ergonomically-designed 5' long horizontal powered hopper with a 42" load height

Mechanical drive system with overload detection

Adjustable crank stroke capable of forming 2" to 8" (50mm to 200mm) deep trays
Nordson ProBlue hot melt glue system
Allen-Bradley PLC control system with touch screen HMI
Fully-interlocked barrier guard package
Many options available upon request

Options

Washdown construction
Servo or mechanical control
Tuck or glue style cartons
Additional hand load area
Marking and coding systems
Allen-Bradley PLC and HMI

Applications

Retail ready, display ready packaging
Beverage
Consumer products
Frozen foods
Meat and poultry
Refrigerated fresh food
Club store packaging

Case Dimensions

A: 16.25" - 36" (415mm - 915mm)
B: 8.25" - 25.75" (210mm - 655mm)
C: 15" - 26" (380mm - 660mm)
D: 7" - 18" (180mm - 455mm)
E: 1.5" - 8" (40mm - 200mm)

Specifications

Electrical: 230/460 VAC, 60Hz, 3 phase
Air: 10 CFM, 95 psi