

#### **Professional Packaging Systems**

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

#### **Contact**

Our Packaging Experts solutions@propac.com 888-318-0083

# nVenia Arpac PC-2000 Intermittent Wrap-Around Case Packer



#### At a Glance

- High-performance intermittent motion wrap-around packer
- Up to 20 cases per minute
- Reduce labor, increase productivity, reduce costs
- Dual opposing vacuum case opening system

Buy your trays and cases from us, and get a discount on this Arpac case erector!

#### Pricing

#### Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

### Wrap-Around Cases at 20 per Minute

The nVenia Arpac PC-2000 is a high-performance intermittent motion wrap-around case and tray packer capable of reaching speeds of up to 20 cases or trays per minute.

The PC-2000 uses up to 20% less corrugated material as compared to regular slotted cases (RSCs) resulting in significant annual material savings. This rugged machine reduces labor, increases productivity, reduces packaging costs and integrates easily into new or existing packaging lines.

The PC Series packers work well with many tapes of packages. The system collates the products, loads the corrugated cases or trays and closes them with hot-melt glue.

### Features of the PC-2000

Speeds of up to 20 cases or trays per minute

Uses up to 20% less corrugated material as compared to regular slotted case (RSC)

Works well with metal cans, paper cans, glass jars, glass bottles, plastic jars and plastic bottles Provides tight packages minimizing the need for partitions while protecting glass containers from damage

Options allow for automatic insertion of partitions/dividers for the ultimate in product protection Easily adjusts to varying product sizes, speeds and product patterns

Runs trays and wrap-around cases

Manuafacturer's joint, inside or outside

Rugged chain drive construction for maximum durability

Smooth infeed pneumatic clamp and push collation provides easy product control

Toppled product sensors alert operator protecting against product jams

Case or tray forming lugged conveyor for versatile operations

Nordson ProBlue series hot melt adhesive system

Positive engagement compression sections provide additional pressure for flap folding

### **Options**

Dedicated glue nozzles for quicker product changeover Additional blank feed capacity magazine Servo driven product collation

### **Case Sizes**

Width (across machine): 7" to 23.2" Length (flow direction): 3.2" to 15.3"

Height: 4.7" to 14.7"

## **Corrugated Requirements**

B flute Kraft corrugation

Burst strength: 150 or 200 lb per square inch

Balanced outside and inside liners to avert warped blanks Minimum combined weight facings: 98 lb per square inch

### **Machine Specifications**

Speed: Up to 20 trays per minute Electrical: 240 or 480V, 3Ph, 60Hz

Air: 80 psi, 20 CFM