

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

Contact

Our Packaging Experts solutions@propac.com 888-318-0083

BestPack ELVS Automatic L-Type Suction Cup Case Erector



At a Glance

- Up to 15 cases per minute
- Quick and easy changeover
- Heavy-duty 3mm CNC cut and welded frame

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Simple High-Performance Case Erecting

The BestPack ELVS case erector is an innovative, high-performance carton erector/sealer. This erector is built for heavy usage with quick and simple carton size changeover. There are no tools required for carton size changeover. The ELVS handles a wide range of carton sizes.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty 3mm CNC cut and welded frame including upper welded legs.

Quick and easy changeover.

Size adjustment screw drive counter for the hopper height position and carton width.

Size adjustment screw drive counter for the carton length.

Power feed hopper.

Hopper length of 40" for carton capacity.

Side belt drive with high-speed motors.

Capable of interchanging 2" or 3" BestPack pop-out high-speed tape head.

Low tape / no tape on carton / no cut sensors with malfunction alarm with three-colored light.

Manual jog button for step-by-step activation of all movements.

Heavy-duty maintenance free oil-less air cylinder.

Vacuum pump suction cup system.

Allen-Bradley PLC logic. Carton on demand logic. Heavy-duty peg legs. Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Spare parts kit Allen Bradley PLC with ethernet capability Exit conveyor Food grade 304 stainless steel Spare tape head

Power & Air

Power: 110 Volts, 60 Hz, 20 Amp Air: 80 psi, 10 scfm

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Case per Minute	Shipping Weight
ELVSL21-2 2" Tape Head	100.8"L x 83.0"W x 64.3"H	8.0" - 20.0"	5.0" - 14.5"	3.0" - 14.0"	25.5" - 31.5"	Up to 15	1800 lbs
ELVSL21-2H 2" Tape Head	100.8"L x 83.0"W x 64.3"H	8.0" - 25.0"	5.0" - 20.0"	3.0" - 21.5"	25.5" - 31.5"	Up to 15	1800 lbs
ELVSR21-2H 2" Tape Head	100.8"L x 83.0"W x 64.3"H	8.0" - 25.0"	5.0" - 20.0"	3.0" - 21.5"	25.5" - 31.5"	Up to 15	1800 lbs
ELVSL21-3H 3" Tape Head	100.8"L x 83.0"W x 64.3"H	8.0" - 25.0"	5.0" - 20.5"	3.0" - 21.5"	25.5" - 31.5"	Up to 15	1800 lbs
ELVSR21-3H 3" Tape Head	100.8"L x 83.0"W x 64.3"H	8.0" - 25.0"	5.0" - 20.5"	3.0" - 21.5"	25.5" - 31.5"	Up to 15	1800 lbs