



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack ESHB Automatic Straight Feed Suction Cup Case Erector

At a Glance

- Up to 10 cases per minute
- Designed for square cartons
- Heavy-duty 3mm CNC cut and welded frame

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Simple High-Performance Erector for Square Cases

The BestPack Packaging ESHB is an innovative high-performance carton erector/sealer using a bottom carton pull system in the hopper. The ESHB is designed for RSC cartons where both L x W have the same measurements (square cartons) and also standard rectangular cartons. The ESHB erector is built for heavy usage with quick and simple carton size change over.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty 3mm CNC cut and welded frame including upper welded legs.

Carton straight fed from the hopper / carton bottom pulled.

Manual jog button for step-by-step activation of all movements to confirm proper size changes.

Quick easy manual length, width and height adjustments.

Tape head side seal adjustment.

Venturi suction cup system.

Hopper holds 70-100 cartons depending on the carton.

Output: up to 15 cartons per minute depending on carton sizes and ranges.

Variable speed Allen-Bradley PLC logic.

Heavy-duty maintenance free oil-less.

Air cylinder interlock safety gates where needed.

Alarm system for low tape / no tape on carton / no cut sensors with malfunction jam detection and three-colored warning light carton on demand logic with photo eye.

Capable of interchanging 2" or 3" BestPack pop-out high-speed tape heads.

Carton is righted as the carton leaves the erector and drops.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Spare parts kit

Allen Bradley PLC with ethernet capability

Automatic tape head center seal adjustment

Food grade 304 stainless steel

Exit conveyor

Spare tape head

Power & Air

Power: 110 Volts, 60 Hz, Single Phase

Air: 100 psi, 10+ scfm

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Case per Minute	Shipping Weight
ESHB11-2 2" Tape Head	126.0"L x 75.0"W x 79.0"H	6.0" - 25.5"	6.0" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 10	2425 lbs
ESHB11-3 3" Tape Head	126.0"L x 75.0"W x 79.0"H	6.0" - 25.5"	6.0" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 10	2425 lbs