

Professional Packaging Systems

2010 S. Great Southwest Parkway Grand Prairie, Texas 75051 www.ProPac.com

Contact

Our Packaging Experts solutions@propac.com 888-318-0083

BestPack ESHT Automatic L-Type Suction Cup Case Erector



At a Glance

- Up to 10 cases per minute
- Top carton pull system designed for large cartons
- Heavy-duty 3mm welded frame

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Simple High-Performance Case Erecting

The BestPack Packaging ESHT is an innovative high-performance carton erector/sealer using a top carton pull system. This design allows for large cartons that can be difficult to erect and yet still handles a wide range of carton sizes. The ESHT erector is built for heavy usage with quick and simple carton size change over. Optional automatic infeed conveyors are available for pre-stacked cartons yet to be erected.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty 3mm welded frame.

Carton straight fed from the hopper / carton top pulled.

Manual jog button for step-by-step activation of all movements to confirm proper size changes.

Quick easy manual length, width and height adjustments.

Tape head side seal adjustment.

Venturi suction cup system.

Hopper holds 70-100 cartons depending on the carton.

Output: up to 10 cartons per minute depending on carton sizes and ranges.

Variable speed.

Allen-Bradley PLC Logic.

Heavy-duty maintenance free oil-less air cylinder.

Interlock safety gates where needed.

Alarm system for low tape / no tape on carton / no cut sensors with malfunction jam detection and three-colored warning light.

Carton on demand logic with photo eye.

Capable of interchanging 2" or 3" BestPack pop-out high-speed tape heads.

Carton is righted as the carton leaves the erector and drops.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Spare parts kit
HMI display touch screen
Pre-stacked automatic carton infeed conveyor
Allen Bradley PLC with ethernet capability
Automatic tape head center seal adjustment
Food grade 304 stainless steel
Exit conveyor
Spare tape head

Power & Air

Power: 110 Volts, 60 Hz, Single Phase

Air: 100 psi, 10+ scfm

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Case per Minute	Shipping Weight
ESHT22-2 2" Tape Head	198.1"L x 86.2"W x 83.1"H	12.0" - 30.0"	8.0" - 24.0"	6.0" - 20.0"	25.5" - 31.5"	Up to 10	3450 lbs
ESHT22-3 3" Tape Head	198.1"L x 86.2"W x 83.1"H	12.0" - 30.0"	8.0" - 24.0"	6.0" - 20.0"	25.5" - 31.5"	Up to 10	3450 lbs