



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Little David CF-25T Automatic Case Former



At a Glance

- Heavy duty automatic case former
- Load on-the-fly blank hopper
- Small foot print
- Chain and lug drive ensures a square box, eliminating stalling
- Quick, simple changeover

Buy your cases from us, and get a discount on this Little David case former!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Heavy Duty Compact Automatic Case Former

The Little David CF-25T fully automatic case former is designed to form and bottom-seal cases at speeds up to 15 per minute. The CF-25T case erecting system is ideal for production lines that require more throughput than manual case forming can provide. This versatile box former creates instant labor savings, and increases production for a wide range of medium-speed packaging lines.

Features of the CF-25T

- Up to 10 cases per minute (15 CPM with upgrade)
- Patented load on-the-fly blank hopper
- Powered hopper holds 150 cases
- Reliable case transfer with powered vacuum system
- Small footprint
- Positive chain and lug drive system ensures a square box, eliminates box stalling
- Interlocking safety gates restrict access to moving parts
- Quick, simple changeover requires no tools
- Load-on-the-fly hopper
- Heavy duty steel construction
- Allen Bradley PLC
- Pneumatically folds flaps
- Calibrated scales

Options

- High speed upgrade
- Several tape cartridge options

- Spare parts kit
- Special electrics
- Custom conveyor height
- Custom color
- Casters
- Low hopper warning
- Low tape warning
- Box jam warning
- Leg extension
- Stainless steel
- Available in CE, NEMA 4, and NEMA 12
- Cold room package
- Autocentral lube system
- Leveling pads
- Air dryer
- Mobile control station

Case Dimensions

- Length: 6" - 16" (152mm - 406mm)
- Width: 6" - 14" (152mm - 355mm)
- Height: 4" - 12" (102mm - 305mm)
- Certain combinations cannot be processed

Tape Specifications

- Any commercially acceptable brand of pressure sensitive tape
- Width: 1.5" - 2" (38mm - 51mm), 3" (76mm) optional
- Roll Length: up to 2000 yards (1829m)
- Roll OD: Max 15" (381mm) on a 3" (76mm) core

Machine Dimensions

- Width: 75.125" (191 cm)
- Depth: 43.25" (110 cm)
- Height: 75.75" (192 cm)

Specifications

- Electrical: 110 VAC, 60Hz, Single phase, 3 Amps (other voltages available)
- Air: 14 SCFM at 85 psi
- Weight: 1,100 lbs (499kg) not crated