



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# Little David CF-25 SB Side Belt Automatic Case Former



## At a Glance

- Side belt drive for cases as narrow as 3.5 inches
- Heavy duty automatic case former
- Load on-the-fly blank hopper
- Small foot print
- Quick, simple changeover

Buy your cases from us, and get a discount on this Little David case former!

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Heavy Duty Compact Automatic Case Former

The Little David CF-25 SB fully automatic case former is designed to form and bottom-seal cases at speeds up to 15 per minute. With a minimum case width of 3.5", this side belt case erector was developed in response to needs from the co-packer, electronics, personal care, and pharmaceutical industries.

Allen Bradley Micro 820 PLC features Ethernet connectivity, sensor functionality, jam detection, and photo eye that will detect box back up in case sealer.

Eaton HMI features machine diagnostics and warnings, ethernet port, case set up instructions, storage for up to 10 case size set-up parameters, and dual languages.

## Features of the CF-25 SB

Up to 10 cases per minute (15 CPM with upgrade)

Patented load on-the-fly blank hopper

Powered hopper holds 150 cases

Boxes are mechanically squared at side belt entrance, and maintain squareness due to common shaft driven belt speeds.

Small footprint

Positive chain and lug drive system ensures a square box, eliminates box stalling

Interlocking safety gates restrict access to moving parts

Quick, simple changeover requires no tools

Heavy duty steel construction

Allen Bradley PLC  
Pneumatically folds flaps  
Calibrated scales

## Options

High speed upgrade  
Several tape cartridge options  
Spare parts kit  
Special electrics  
Custom conveyor height  
Custom color  
Casters  
Low hopper warning  
Low tape warning  
Box jam warning  
Leg extension  
Stainless steel  
Available in CE, NEMA 4, and NEMA 12  
Cold room package  
Autocentral lube system  
Leveling pads  
Air dryer  
Mobile control station

## Case Dimensions

Length: 6" - 16" (152mm - 406mm)  
Width: 3.5" - 14" (88.9mm - 355mm)  
Height: 4" - 12" (102mm - 305mm)  
Certain combinations cannot be processed

## Tape Specifications

Any commercially acceptable brand of pressure sensitive tape  
Width: 1.5" - 2" (38mm - 51mm), 3" (76mm) optional  
Roll Length: up to 2000 yards (1829m)  
Roll OD: Max 15" (381mm) on a 3" (76mm) core

## Machine Dimensions

Width: 75.125" (191 cm)  
Depth: 43.25" (110 cm)  
Height: 75.75" (192 cm)

## Specifications

Electrical: 110 VAC, 60Hz, Single phase, 3 Amps (other voltages available)  
Air: 14 SCFM at 85 psi  
Weight: 1,250 lbs (567kg) not crated