



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Little David CF-50T Automatic Case Former

At a Glance

- High performance, innovative automatic case former
- Forms up to 20 cases per minute
- Tool-less changeover
- Heavy duty steel construction

Buy your cases from us, and get a discount on this Little David case former!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



High Performance Heavy Duty Case Erector

The Little David CF-50T is the highest quality, most cost effective case former in the industry. This high performance, innovative machine is designed to automatically form, fold, and bottom seal RSC corrugated cases. The CF-50T easily folds a variety of corrugated cases, from double wall to recycled material. This powerhouse case erector can form up to 20 cases per minute.

The CF-50T heavy duty steel construction endures the most rigorous industrial environments. The CF-50T requires minimal operator training, decreasing your operating costs. Tool-less changeover features make it simple to switch from one box size to another.

Features of the CF-50T

Up to 20 cases per minute, depending on case size and corrugated quality

Chain lug drive

Powered hopper

Small footprint

Positive drive system

Quick changeover

Heavy duty steel construction

Allen Bradley PLC

Pneumatic tuckers

Calibrated scales

Tape Specifications

Any commercially acceptable brand of pressure sensitive tape

Width: 1.5" - 2" (38mm - 51mm), 3" (76mm) optional

Roll Length: up to 2000 yards (1829m)

Roll OD: Max 15" (381mm) on a 3" (76mm) core

Options

Partial stainless

Spare parts kit

Special electrics

Box jam warning

Low tape warning

Low hopper warning

Casters

Tape detection

Extended Legs

Guarding package

Stainless steel

Automatic central lube

Available in CE, NEMA 4

Extended capacity powered hopper

Leveling pads

Air dryer

Mobile control station

Machine Dimensions

Width: 128" (325 cm)

Depth: 41" (104 cm)

Height: 54" (137 cm)

Specifications

Electrical: 110 VAC, 60Hz, single phase, 10 Amps (other voltages available)

Air: 11 SCFM at 80 psi

Weight: 1000 lbs (453.6 kg) not crated

Standard Discharge Height: 23 1/4 inches (50.7 cm)

Case Size Range

Model	Case Length	Case Width	Case Height
CF-50T	7" - 24"	6" - 16"	4" - 20"
CF-50TXL	8" - 24"	6" - 20"	4" - 20"