



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Little David SP-304R BO Random Bottom Only Case Former

At a Glance

- Designed for random sized case forming and packing
- Great for order fulfillment centers
- Innovative T-rail infeed table for fast case processing
- Bottom major flap folding bars
- Reliable simple operation
- Heavy duty steel construction

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Bottom Only Side Belt Former for Random Sized Cases

The Little David SP-30R BO sealer provides a consistent seal on randomly sized boxes with side belts that move to the case width, and moves the case through a folding area and right over the tape cartridge.

With an innovative extended T rail packing table, the operator has space to form and pack the case prior to sealing.

The tool-less quick release wipe rollers and knife blade accompanying the CaseLocker 60 tape cartridge are patent-pending.

Features

Improve productivity and throughput by maximizing operator efficiency

Eliminate ergonomic risk factors by reducing operator fatigue and repetitive motion syndrome

Extensive case range

Movable control station

Easy access motors, electrics, and belts

Plug in operation

Minimal operator training required

Sealed drive system

CaseLocker ST tape cartridge requires no lubrication

Alleviates twisting motion known to cause carpal tunnel syndrome
Self-centering belts
Continuous belt drive
Operating Speed: Up to 72' per minute (18.3 m/min)
Seals with pressure sensitive tape
Processes 32 ect single wall to 44 ect double wall boxes

Case Dimensions

Length: 8" - maximum based on anvil
Width: 4.5" - 20"
Height: 3.5" - infinite

Machine Dimensions

Width: 79.77" (202.6 cm)
Depth: 37.65" (95.6 cm)
Height: 24.25" to 30.25" (61.6 to 76.8 cm)

Specifications

Electrical: 120 VAC, 60Hz, Single phase, 15 Amps (other voltages available)
Air: 3 SCFM at 45 psi
Weight: 570 lbs (258 kg) uncrated