



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

A-B-C 121 Tablock High-Speed Case Slitter Sealer

At a Glance

- Tablock high-speed case slitter sealer
- High speed case sealing to 50 cpm
- Wide case range
- Seal with tape or hot melt adhesive

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this A-B-C case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Tablock High-Speed Case Slitter Sealer Sealing 5-50 CPM

The A-B-C 121 case slitter efficiently slits the tabs of tablock cases then gently and smoothly closes the flaps and seals the case in one continuous operation. This case sealer has proprietary features that compensate for inherent case variations to ensure reliable operation on high-speed production runs. A-B-C's innovative engineering and quality construction place this tablock case slitter and sealer a cut above the competition.

Machine Features

Continuous, high-speed operation
Compact, in-line design for easy installation
Tape and adhesive sealing models available
Speeds to 50 cpm

Benefits

Positive Case Feed: The automatic metering belt and gate release mechanisms ensure proper spacing and control of cases during high-speed operation. High-traction belting provides positive case transfer.

Precision Tab Slitting: The simple and forgiving tab slitters automatically accommodate the inherent variations in each case. The slitters precisely contact the case, lift and slit the tabs, in continuous, mechanical motion.

Accurate Flap Folding: Floating guides gently sweep the inner flaps upward to be folded by timed mechanical flap folders. Outer flap closing is provided by A-B-C's production-proven contoured cast

aluminum flap folders.

Square, Securely Sealed Cases: The compression section has powered top and bottom belts backed by steel rollers that are designed to seal cases squarely. The top motorized compression belt is backed by spring-loaded rollers that ensure proper sealing regardless of case variations.

Case Range

Length: 10" - 22"

Width: 9" - 17"

Height: 7" - 17"

Options

Repeatable position indicators on adjustment shafts

Machine Specifications

High Performance Features:

Automatic case feed

Automatic metering and gate release infeed

High traction belt case drive

Mechanical timed inner flap folders

Cast aluminum outer flap folders

Powered compression section with top and bottom motorized belts

Gull-wing style high visibility doors

Low voltage control circuit transformer

Convenient power on-off button

Reduced Maintenance Features:

Heavy stainless steel frame

Maintenance-free sealed bearings

Main gear drive in sealed oil bath

Self-lubricating air cylinders

Automatic water eliminator

Specifications:

Case range: RSC cases

Electrical: Primary 440/220v, 60 Hz, 3 Phase

Air: .71 SCFM per cycle at 75 psi

Mechanical: Main drive 1.5 hp motor

Metering belt: 1/3 hp motor

Flap lifters: (2) 1/2 hp motors

Speed: Up to 50 cases per minute

Machine weight: 4,000 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.