



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

A-B-C 236 Top Hot Melt Adhesive Case Sealer

At a Glance

- Midrange case sealing at 15-25 cpm
- Compact footprint, only 10 feet long
- Seal with hot melt adhesive

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this A-B-C case taper!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.



Adhesive Case Sealing Up to 25 CPM

The A-B-C 236 case sealer is a compact machine built for top production. Its heavy steel box frame and production-proven components make A-B-C case sealers the gold standard of 24/7 reliability. With a low-maintenance design and quick change versatility, this machine will provide a solid return on your case sealing investment.

Machine Features

- Super small footprint (only 8' long) for easy installation
- Non-stop case feed whether cases are spaced or back-to-back
- Flexible compression rollers ensure well-sealed cases
- Seal top flaps with adhesive at speeds to 25 cpm

Benefits

Built for Production: This adhesive case sealer's painted steel frame is welded and bolted for strength, and the upper operating mechanisms are secured to the frame by a solid rack and gear system. Drive shafts are solid 1-1/4" steel. The clear guard doors combine maximum visibility with total protection as they stop production when opened. All these production features, built into a compact case sealer, make the A-B-C 236 adhesive case sealer the solution for reliable top case sealing.

Nonstop Case Feed for Reliable Sealing: Nonstop case feed keeps your line moving at maximum speed. Cases may feed to the sealer back to back or spaced, and the metering belt automatically spaces each case for synchronized flap folding and sealing.

Positive Flap Tucker for Smooth Operation: After the front inner flap is closed by a stationary closer, the

rear inner flap is positively closed by the powered flap tucker. After adhesive application, contoured flap folders gently close the outer case flaps at the scoreline, while a positioning bar rides between the flaps to prevent flap overlap. This ensures square cases even when running cases with poor scores.

No-Crush Compression Rollers Provide Secure Adhesive Sealing and Square Cases: This compression section has flexible rollers that compress the case flaps securely to provide square, well-sealed cases that run efficiently in automatic palletizing operations.

Case Range

Length: 8" - 24"

Width: 6" - 16"

Height: 4.5" - 18"

Machine Specifications

High Performance Features:

Steel frame construction

Metering roller infeed automatically feeds cases spaced or back to back

Rotating flap tucker folds trailing inner flap

Automatic minor flap closing

Contoured cast aluminum flap folders

Top quality hot melt adhesive applicator/ tape applicator

No-crush flexible compression rollers that compress case flaps securely to provide square, well-sealed cases

Sliding interlocked panel guards

Low voltage control circuit transformer

Adjustable leveling footpads (+/-2")

Convenient power on-off button

Substantial 1 hp drive motor powers sealer

Reduced Maintenance Features:

Rapid-adjust cranks for case change

Maintenance-free sealed bearings

Self-lubricated pneumatic tucker

Adjustable leveling footpads

Automatic water eliminator

Specifications:

Case range: RSC, CSSC cases

Electrical: Primary 230 or 460v, 60hz, 3ph, NEMA 12

Mechanical: 1 hp motor

Air: .08 cu. ft. per cycle at 60 psi

Speed: To 25 cases/minute

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.