



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

A-B-C 30T Top & Bottom Tape Sealing Case Sealer

At a Glance

- Tape top and bottom case sealer 5-50 cpm
- Rugged tape case sealer built for production
- Exterior-mounted tape roll for easy refill



Buy your [case sealing tape](#) from Pro Pac, and get a discount on this A-B-C case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Top and Bottom Tape Case Sealing 5-50 CPM

Built for real world production, the A-B-C 30T tape sealer is designed to provide top reliability and efficiency in most challenging case sealing environments. With production-proven features that seal cases squarely and securely, this sealer has long set an industry standard for tape sealing productivity. Built into its heavy stainless steel frame are top quality components to virtually eliminate downtime for maintenance. It's a case sealer that will fulfill your production needs today and in the future.

Machine Features

- Rugged and reliable top & bottom case sealing
- Rotary flap tucker for secure flap closing
- Easy access tape roll for quick replacement
- Designed for the most challenging case sealing requirements
- Seal top flaps with tape at speeds to 50 cpm

Benefits

Built for Production: This tape case sealer is manufactured as a compact, integrated unit, which eliminates vibration that can lead to premature wear. The stainless steel frame is welded and bolted, and the upper operating mechanisms are secured to the frame by a solid rack and gear system. Drive shafts are solid 1-1/4" steel. The flight lugs are forged of cast aluminum for strength, mounted on wear-resistant 1-1/2" pitch flight chain. With a total machine weight of over 2,200 pounds, the Model 30T tape case sealer can handle the toughest production situations. This tape case sealer's sleek stainless steel frame won't rust and never needs painting. The clear, gull-wing doors are a standard feature, not special

order. They are electrically interlocked to stop the sealer when opened, and allow total access to the machine.

No Operator Required: Each case is automatically indexed into the case sealer from your conveyor. As the motor-driven flight lugs transfer the case through the sealer, the top inner flaps are folded by a powered flap tucker. Then, the outer flaps are folded and tape is applied. The case exits the machine sealed, square and ready for palletizing.

Easy Tape Roll Replacement: This tape case sealer offers features that eliminate wasted tape and dramatically reduce lost production time for tape roll changes. Both the top and bottom tape rolls are exterior mounted to allow easy access. The "roll empty" sensor stops the sealer just as the end of the tape comes off the roll. The attendant simply replaces the roll, and attaches the new roll to the tail of the last roll.

Features for Square Cases: A-B-C's exclusive flight lugs push each case at the corners, to square it during transfer. The cast aluminum flap folders are gradually contoured to fold the flaps at the score line then close them smoothly with no flap overlap. Even cases with undefined scores are folded squarely and securely.

Low Maintenance: The rugged construction of the Model 30 tape case sealer is your guarantee that it will run longer with less wear or care. Yet this powerhouse case sealer has additional features to minimize your maintenance tasks. The main drive gear assembly is enclosed in a lubricating oil bath to eliminate gear wear. Sealed bearings and self-lubricated air cylinders never need maintenance. The automatic water eliminator prevents air valve damage caused by water in air lines. When routine maintenance or cleaning is necessary, the gull-wing doors swing out of the way to allow complete machine access.

Quick Changeover: Case size changeover is simple; position a new case at the infeed and use the manual crank adjusts to fit the new case height and width. In minutes, the tape case sealer is back in production.

Case Range

Length: 8" - 24"

Width: 6" - 16"

Height: 4.5" - 18"

Options

Repeatable position indicators on adjustment shafts

Machine Specifications

High Performance Features:

Automatic case feed

Automatic minor flap closing

Heavy-duty flight lug drive

Cast aluminum flap folders

Top quality taping heads: 2" width standard, 3" width also available

Gull-wing style high visibility doors

Low voltage control circuit transformer

Convenient power on-off button

Reduced Maintenance Features:

Heavy stainless steel frame
Exterior mounted tape rolls
Rapid-adjust cranks for case change
Maintenance-free sealed bearings
Main gear drive in sealed oil bath
Self-lubricating air cylinders
Automatic water eliminator

Specifications:

Case range: RSC cases
Electrical: Primary 230 or 440v, 60hz, 3ph
Air: .05 cu. ft. per cycle at 60 psi
Speed: 5 - 50 cases/minute
Tape roll diameter: up to 15-1/2" maximum on 3" diameter core

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.