



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack AQ Automatic Quad Drive Uniform Case Sealer

At a Glance

- Operator-free, uniform in-line case sealer
- Four belt drives
- Closes all top flaps, seals top & bottom of carton
- Carton stability and effective sealing in rugged applications
- Up to 57 cases per minute



Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Quad-Belt Drive Provides Carton Stability and Effective Sealing

The BestPack AQ operator-free case sealer is designed to meet the needs of uniform in-line carton closure applications. The AQ case sealer closes all top flaps and seals the top & bottom of the carton.

Four belt drives are powered by three electric 110V UL approved motors. This quad-belt technology allows for more carton stability and effective sealing in rugged applications.

The AQ is designed with a stable four-column support structure, and uses 45-60 PSI and 4-5 SCFM of air. All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Inline automatic top flap folding

Adjustable bed height from: 22.5" to 30.0"

Width/height adjustment handle can be mounted on either side of the carton sealer

Upper side compression unit

Interlock safety gates in the kicker station

Tape roll lengths: 1000 yd, 1500yd, 2000yd

Heavy-duty 2mm CNC cut and welded frame including upper welded legs

Capable of interchanging 2" or 3" tape heads

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and

noise reduction arm

Options

Spare parts kit

High-speed motor upgrade (Up to 125 feet per minute)

VFD motor upgrade (up to 150+ feet per minute)

Locking heavy-duty casters

Additional safety guarding available

Compatible indexer: ARX model

Power & Air

Power: 110 Volts, 60 Hz

Air: 45-60 psi, 4-5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
AQ12-2 2" Tape Head	70.2"L 26.5"W 68.0"H	8.0" - 25.5"	7.5" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 34	632 lbs
AQ12-2H 2" Tape Head	70.2"L 26.5"W 68.0"H	8.0" - 25.5"	7.5" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 57	632 lbs
AQ12-3 3" Tape Head	70.2"L 26.5"W 68.0"H	8.0" - 25.5"	7.5" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 34	632 lbs
AQ12-3H 3" Tape Head	70.2"L 26.5"W 68.0"H	8.0" - 25.5"	7.5" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 57	632 lbs
AQ22-2 2" Tape Head	77.5"L 33.8"W 73.0"H	8.0" - 27.5"	7.5" - 20.0"	5.5" - 20.0"	23.5" - 30.0"	Up to 34	645 lbs
AQ22-2H 2" Tape Head	77.5"L 33.8"W 73.0"H	8.0" - 27.5"	7.5" - 20.0"	5.5" - 20.0"	23.5" - 30.0"	Up to 57	645 lbs
AQ22-3 3" Tape Head	77.5"L 33.8"W 73.0"H	8.0" - 27.5"	7.5" - 20.0"	5.5" - 20.0"	23.5" - 30.0"	Up to 34	645 lbs
AQ22-3H 3" Tape Head	77.5"L 33.8"W 73.0"H	8.0" - 27.5"	7.5" - 20.0"	5.5" - 20.0"	23.5" - 30.0"	Up to 57	645 lbs
AQ33-3 3" Tape Head	83.0"L 43.0"W 81.0"H	8.0" - 27.5"	7.5" - 27.5"	6.0" - 30.0"	23.5" - 30.0"	Up to 34	657 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.