



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack AS Automatic Side Drive Uniform Case Sealer



At a Glance

- Operator-free, uniform in-line case sealer
- Dual motor side belt drives
- Solid four column support structure
- Carton stability and effective sealing in rugged applications
- Up to 57 cases per minute

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Four Column Support with Side Belt Drives

The BestPack AS operator-free case sealer is designed to meet the needs of uniform in-line carton closure applications. The AS is designed with a solid four column support structure and using dual motor side belt technology. The AS closes all four top flaps and seals the top and bottom of the carton, using 45-60 PSI and 4-5 SCFM of air.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Low tape, no tape no cut sensors.

Adjustable bed height from: 22.5" to 30.0".

Width/height adjustment handle can be mounted on either side of the carton sealer.

Interlock safety gates in the kicker station.

Upper side compression unit.

Tape roll lengths: 1000yd, 1500yd, 2000yd.

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

UL approved electrical parts.

Capable of interchanging 2" or 3" tape heads.

Electrical on/off box can be mounted on either side of carton sealer.

Inline automatic top flap folding.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

- Spare parts kit
- High-speed motor upgrade (Up to 125 feet per minute)
- VFD motor upgrade (up to 150+ feet per minute)
- Locking heavy-duty casters
- Additional safety guarding available
- Compatible indexer: ARX model

Power & Air

- Power: 110 Volts, 60 Hz
- Air: 45-60 psi, 4-5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
AS12-2 2" Tape Head	70.2"L26.5"W68.0"H	6.0" - 25.5"L	6.0" - 14.0"W	6.5" - 20.0"H	22.5" - 30.0"	Up to 34	500 lbs
AS12-2H 2" Tape Head	70.2"L26.5"W68.0"H	6.0" - 25.5"	6.0" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 57	500 lbs
AS12-3 3" Tape Head	70.2"L26.5"W68.0"H	6.0" - 25.5"	6.0" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 34	500 lbs
AS12-3H 3" Tape Head	70.2"L26.5"W68.0"H	6.0" - 25.5"	6.0" - 14.0"	6.5" - 20.0"	22.5" - 30.0"	Up to 57	500 lbs
AS22-2 2" Tape Head	77.5"L33.8"W69.0"H	6.0" - 27.5"	6.0" - 20.0"	5.5" - 20.0"	22.5" - 30.0"	Up to 34	585 lbs
AS22-2H 2" Tape Head	77.5"L33.8"W69.0"H	6.0" - 27.5"	6.0" - 20.0"	5.5" - 20.0"	22.5" - 30.0"	Up to 57	585 lbs
AS22-3 3" Tape Head	77.5"L33.8"W69.0"H	6.0" - 27.5"	6.0" - 20.0"	5.5" - 20.0"	22.5" - 30.0"	Up to 34	585 lbs
AS22-3H 3" Tape Head	77.5"L33.8"W69.0"H	6.0" - 27.5"	6.0" - 20.0"	5.5" - 20.0"	22.5" - 30.0"	Up to 57	585 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.