



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack AS-S Automatic Stainless Side Drive Uniform Case Sealer



At a Glance

- Built with food grade 304 stainless steel for 21 CFR 110 compliance
- Dual motor side belt drives
- Solid four column support structure
- Closes all four top flaps and seals top & bottom of carton
- Up to 34 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Stainless Steel for Case Sealing in Wet Environments

The BestPack AS-S stainless steel operator-free carton sealer is designed to meet the needs of uniform in-line carton closure applications in wet environments. Designed with a solid four column support structure and using dual motor side belt technology, the AS-S closes all four top flaps and seals the top & bottom of the carton, using 45-60 PSI and 4-5 SCFM of air.

All BestPack stainless steel units are built with food grade 304 stainless steel for 21 CFR 110 compliance and available in splash resistant or wash down models.

Features

Heavy-duty 2mm food grade 304 stainless steel welded frame including upper welded legs.

Side belt drive system with 1-piece molded belts and V-belt guide.

Accepts 2" and 3" pop-out BestPack high-speed.

Food grade 304 stainless steel tape heads.

Width/height adjustment handle can be mounted on either side of the carton sealer.

Heavy-duty upper assembly four post system.

Aluminum framed interlock safety gates in the kicker station.

Heavy-duty maintenance free oil-less air cylinders.

Electrical box is mounted on the left side of the sealer.

Adjustable bed height 22.5" to 30.0".

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.

Quality UL approved electrical parts.

Options

Spare parts kit

High-speed motor upgrade (up to 125 feet per minute)

Food grade 304 stainless steel locking heavy-duty casters

Aluminum framed interlock safety gates for the major flap folding and sealing stations

Compatible indexer: ARX Model

Power & Air

Power: 110 Volts, 60 Hz

Air: 45-60 psi, 4-5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

| Model | Machine Dimensions | Case Length | Case Width | Case Height | Conveyor Height | Cases per Minute | Shipping Weight |
|-------------------------|--------------------|------------------|------------------|------------------|-----------------|------------------|-----------------|
| AS12-2S 2" Tape Head | 70.2"L26.5"W68.0"H | 8.0" - 25.5"L | 6.0" - 14.0"W | 6.5" - 20.0"H | 22.5" - 30.0" | Up to 34 | 527 lbs |
| AS12-3S 3" Tape Head | 70.2"L26.5"W68.0"H | 8.0" - 25.5"L | 6.0" - 14.0"W | 6.5" - 20.0"H | 22.5" - 30.0" | Up to 34 | 527 lbs |
| AS22-2S 2" Tape Head | 77.5"L33.8"W69.0"H | 8.0" - 27.5"L | 6.0" - 20.0"W | 5.5" - 20.0"H | 22.5" - 30.0" | Up to 34 | 616 lbs |
| AS22-3S 3" Tape Head | 77.5"L33.8"W69.0"H | 8.0" - 27.5"L | 6.0" - 20.0"W | 5.5" - 20.0"H | 22.5" - 30.0" | Up to 34 | 616 lbs |

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.