



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack AT4E-L Automatic Stainless 4 Edge Case Sealer, L-Turn



At a Glance

- Uniform four-edge case sealing in a wet environment
- Automatic front side feed 90 degree box turn
- Automatically applies pressure sensitive tape, eliminating hand taping
- Heavy-duty 3mm welded 304 food grade stainless steel frame including upper welded legs
- Up to 8 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal Four Case Edges in a Wet Environment

The BestPack AT4E-L operator-free case sealer automatically applies pressure sensitive tape to four outer edges of cartons. The AT4E-L is designed to eliminate costly hand taping of the four outer edges where pilfer-proofing and protection of your product is necessary.

The AT4E-L stainless steel model is designed for uniform edge sealing applications where there is a wet environment. These case tapers are designed with an automatic front side feed 90 degree box turn.

All BestPack stainless steel sealers are made with food grade 304 stainless steel for 21 CFR 110 compliance and include 304 high-speed stainless steel tape heads. Units are available for either splash resistant or wash-down applications. This unit is also available in standard finish.

Features

Heavy-duty 3mm welded 304 food grade stainless steel frame including upper welded legs.

Seals all four outside carton edges including all corners.

In-line 90 degree carton turner.

Top and bottom four belt drive system with 1-piece molded belts and V-belt guide.

Top and bottom four 3" pop-out BestPack high-speed 304 stainless steel tape heads.

Low tape / no tape on carton / no cut sensors with malfunction alarm and three color light.

Motor drive uniform height adjustment.

Heavy-duty upper assembly four post system.

Heavy-duty maintenance free oil-less air cylinder.
Aluminum framed interlock safety gates where needed.
Tape roll lengths: 1000 yd.
Quality UL approved electrical parts.

Options

Left side infeed or a right side infeed
Infeed/exit conveyor with L-bracket stabilizer
Spare parts kit
304 stainless MSD or 304 stainless AS-S

Power & Air

Power: 110 Volts, 60 Hz
Air: 80 psi, 10 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
AT4EL22-3S 3" Tape Head	78.9"L 48.5"W 63.0"H	10.3" - 23.5"	9.8" - 23.5"	9.8" - 23.5"	Set at order	Up to 8	1550 lbs
AT4ES22-3 3" Tape Head	110.3"L 49.8"W 60.5"H	10.3" - 23.5"	9.8" - 23.5"	9.8" - 23.5"	Set at order	Up to 8	1970 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.