



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack ATRFXU Automatic Uniform Fruit Box Case Sealer



At a Glance

- Handles the heavy-duty needs of HSC produce carton usage
- Seals cartons of oranges, lemons, potatoes, and other produce
- Automatically applies pressure sensitive tape, eliminating hand taping
- Heavy-duty 3mm CNC cut and welded frame including upper welded legs
- Up to 38 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal Four Case Edges in a Wet Environment

The BestPack ATRFXU operator-free case sealer handles the heavy-duty needs of HSC produce carton usage. Using pressure sensitive tape to seal cartons, the ATRFXU is designed for cartons of oranges, lemons, potatoes, and other produce.

The ATRFXU case sealer has four stations: an indexer station, a positive outer sleeve lifting station with vibration that is activated only if the outer sleeve does not lift, a flap folding station, leading to a final station which seals the top and bottom flaps, leaving the top and bottom flaps sealed but not tabbed together.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty 3mm CNC cut and welded frame including upper welded legs.

Unique positive outer sleeve lifting station.

Rear minor flap side action kicker.

Heavy-duty maintenance free oil-less air cylinder.

Capable of interchanging 2" or 3" high-speed BestPack tape heads.

High-speed top and bottom belt drive.

Quick change belt drive assembly tracks.

Belt drives are equipped with a V guide.

Self centering guide rails.

Width/height adjustment handle can be mounted on either side of the carton sealer.

Upper side compression unit.

Interlock safety gates.

Tape roll lengths: 1000 yd, 1500yd, 2000yd.

Quality UL approved electrical parts.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Four Stations in One Sealer

Indexer station.

Positive outer sleeve vibrating lifting station, that performs only if the outer sleeve of the carton fails to lift.

Flap fold station closes the top flaps.

Final station seals the top and bottom flaps leaving the top and bottom flaps sealed but not tabbed together.

Options

Spare parts kit

Low and/or no tape alarm & sensor system

Infeed/exit conveyor with L-bracket

Food grade 304 stainless steel

Power & Air

Power: 208 Volts, 3 Ph

Air: 90 psi, 8 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
ATFXU22-2 2" Tape Head	107.5"L 40.3"W 58.7"H	16.7" - 23.5"	11.2" - 15.6"	5.2" - 10.5"	24.0" - 30.5"	Up to 38	1098 lbs
ATFXU22-3 3" Tape Head	107.5"L 40.3"W 58.7"H	16.7" - 23.5"	11.2" - 15.6"	5.2" - 10.5"	24.0" - 30.5"	Up to 38	1098 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

