



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MBD-S Stainless Steel Manual Bottom Drive Uniform Case Sealer



At a Glance

- Dual bottom belt drive
- 304 stainless steel construction approved food grade applications
- Four adjustable legs for height modification
- Exclusive 2 inch or 3 inch pop-out pressure-sensitive high-speed tape heads
- Telescopic mast design
- Up to 20 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Stainless Bottom Belt Case Sealer for Wet Environments

The BestPack MSD-S stainless steel semi-automatic uniform case sealers are designed to seal cases in wet environments. Units are available for either splash resistant or wash-down applications. The two bottom belts are driven by one bottom drive electric 110V UL approved motor.

The BestPack MBD-S food grade 304 stainless steel case taper is approved food grade applications. The tape head also comes standard in food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty 2mm food grade 304 stainless steel welded frame including upper welded legs.

Offset top tape heads for top and bottom sealing cartons down to 3.0" tall.

Bottom belt drive system with 1-piece die molded belts and V-belt guide.

Bottom belt drive system also includes idler rollers behind the belts.

3" tape head unit accepts either 2" and 3" pop-out BestPack high-speed tape heads.

Top mast design with screw drive shafts and an upper side compression unit.

Adjustable bed height from 23.5" to 30.0".

Width adjustment uses self-centering side guide rails.

Height adjustment handle can be mounted on either side of carton sealer.

Electrical on/off box can be mounted on either side of the sealer.

Tape roll lengths: 1000yd 1500yd & 2000yd.

Extra 4" carton height adjustment available on upper assembly.

Quality UL approved electrical parts.

Options

Food grade 304 stainless steel infeed/exit conveyor with L-bracket stabilizer

Food grade 304 stainless steel heavy-duty dual locking casters

Spare parts kit

High-speed motor upgrade (up to 125 feet per minute)

Aluminum frame interlock safety gates

Motorized height adjustment

Power & Air

Power: 110 Volts, 60 Hz

Air: None

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
MBD22-2S 2" Tape Head	42.0"L x 28.8"W x 70.3"H	6.0" - ∞"	6.5" - 20.0"	3.0" - 20.25"	23.5" - 30.0"	Up to 20	320 lbs
MBD22-3S 3" Tape Head	42.0"L x 28.8"W x 70.3"H	6.0" - ∞"	7.5" - 20.0"	3.0" - 20.25"	23.5" - 30.0"	Up to 20	320 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.