



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MBD Manual Bottom Drive Uniform Case Sealer



At a Glance

- Dual bottom belt drive
- Four adjustable legs for height modification
- Exclusive 2 inch or 3 inch pop-out pressure-sensitive high-speed tape heads
- Telescopic mast design
- Up to 30 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Quad-Belt Drive Provides Carton Stability and Effective Sealing

BestPack MBD bottom belt case sealers are operator-fed, designed to efficiently tape tops and bottoms of uniform cartons.

Two bottom belts are powered by an 110V UL-approved electric motor. The MBD Series is also designed with four adjustable legs for quick and easy height modification to suit the needs of your production lines. Dual telescopic masts allow for an extra 4" carton height extension on the upper assembly.

The BestPack MBD line incorporates exclusive 2" or 3" pop-out pressure-sensitive high-speed tape heads with BestPack's patented tab adjustment. All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Two bottom belt drive.

Telescopic mast design.

Extra 4" carton height adjustment available on upper assembly.

Adjustable bed height for MBD22-2 & MBD22-3: 23.5" to 30.0".

Upper side compression unit.

Height adjustment handle can be mounted on either side of carton sealer.

Guide rail centering mechanism.

Tape roll lengths: 1000yd 1500yd & 2000yd.

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

Sealer available in 2" or 3" tape heads.

Exclusive 2" or 3" pop-out pressure.

Sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Electrical on/off box can be mounted on either side of the sealer.

Options

Spare parts kit

Locking heavy-duty casters

Interlock safety gates

Food grade 304 stainless steel

Infeed/exit conveyor w/ unique L-bracket stabilizer

Power & Air

Power: 110 Volts, 60 Hz

Air: None

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
MBD22-2 2" Tape Head	42.0"L 28.8"W 70.3"H	6.0" - ∞"	6.5" - 20.0"	3.0" - 20.25"	23.5" - 30"	Up to 20	310 lbs
MBD22-3 3" Tape Head	42.0"L 28.8"W 70.3"H	6.0" - ∞"	7.5" - 20.0"	3.0" - 20.25"	23.5" - 30"	Up to 20	310 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.