



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MQ Manual Quad Drive Uniform Case Sealer



At a Glance

- Quad-belt drive, two on the side and two on the top
- Effectively seal heavy-duty and unstable cases
- Adjustable bed height from 20.5 inches to 30 inches
- Powered by three 110V UL-approved electric motors
- Up to 50 cases per minute

Buy your [case sealing tape](#) from Pro Pac, and get a discount on this BestPack case taper!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Two Belts on the Side and Two on the Top Securely Seal Unstable Cartons

BestPack MQ case tapers are designed to effectively fulfill heavy-duty and unstable sealing needs. Featuring a quad-belt drive, two on the side and two on the top, the MQ sealers will securely move unstable cartons.

These BestPack MQ sealers are powered by three 110V UL-approved electric motors. The mast allows for an extra 4" carton height extension on the upper assembly.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Fully adjustable.

Four belt drive - 2 top & 2 side.

Adjustable bed height from 20.5" to 30".

Electrical on/off box can be mounted on either side of the sealer.

Width/height adjustment handle can be mounted on either side of the carton sealer.

Tape Roll Lengths: 1000 yd, 1500 yd, 2000 yd.

Heavy-duty frame.

UL approved electrical parts.

Capable of interchanging 2" or 3" tape heads.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and

noise reduction arm.

Options

Spare parts kit
Spare tape head
High-speed motor upgrade (up to 125 feet per minute)
Heavy-duty locking casters
Motorized height and/or width adjustment
Interlock safety gates
Food grade 304 stainless steel
Short infeed/exit conveyor with L-bracket

Power & Air

Power: 110 Volts, 60 Hz

Air: None

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
MQ22-2 / 3 2" or 3" Tape Head	39.5"L x 36.0"W x 55.5"H	6.0" - ∞"	7.5" - 21.0"	4.5" - 20.5"	20.5" - 30.0"	Up to 40	385 lbs
MQ22-2H / 3H 2" or 3" Tape Head	39.5"L x 36.0"W x 55.5"H	6.0" - ∞"	7.5" - 21.0"	4.5" - 20.5"	20.5" - 30.0"	Up to 50	385 lbs
MQ23-2 / 3 2" or 3" Tape Head	39.5"L x 36.0"W x 68.0"H	6.0" - ∞"	7.5" - 21.0"	4.5" - 30.0"	20.5" - 30.0"	Up to 40	420 lbs
MQ22-3H / 3H 2" or 3" Tape Head	39.5"L x 36.0"W x 68.0"H	6.0" - ∞"	7.5" - 21.0"	4.5" - 30.0"	20.5" - 30.0"	Up to 50	420 lbs
MQ33-3 3" Tape Head	39.5"L x 43.0"W x 81.0"H	6.0" - ∞"	7.5" - 30.0"	6.0" - 30.0"	20.5" - 30.0"	Up to 25	542 lbs
MQ33-3H 3" Tape Head	39.5"L x 43.0"W x 81.0"H	6.0" - ∞"	7.5" - 30.0"	6.0" - 30.0"	20.5" - 30.0"	Up to 32	542 lbs
MQ44-3 3" Tape Head	39.5"L x 53.0"W x 91.0"H	6.0" - ∞"	7.5" - 40.0"	6.0" - 40.0"	20.5" - 30.0"	Up to 25	600 lbs
MQ44-3H 3" Tape Head	39.5"L x 53.0"W x 91.0"H	6.0" - ∞"	7.5" - 40.0"	6.0" - 40.0"	20.5" - 30.0"	Up to 32	600 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.