



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MS1E Manual Side Drive 1-Edge Case Sealer



At a Glance

- 1-edge high-speed semi-automatic uniform sealer
- Operator-fed standard
- Operator-free with addition of matching adjustable indexer
- Heavy-duty 2mm CNC cut and welded frame including upper welded legs
- Up to 45 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

1-Edge High-Speed Semi-Automatic Case Sealing

The BestPack MS1E case sealer is a 1-edge high-speed semi-automatic uniform sealer using pressure sensitive tape.

The MS1E is available in either 1-edge top left or 1-edge top right applications. This 1-edge case sealer is an operator-fed sealer that can be converted to be operator-free with the addition of a matching adjustable indexer.

Depending on the motor drive speed used the MS1E can reach cartons speeds of over 45 cartons per minute. This sealer excels at one edge sealing clamshell, flap tuck and flap edge lock type cartons both in corrugated and chipboard.

Features

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

Side belt drive.

Top 1 edge seal.

Adjustable bed height from 22.5" to 30.0".

Exclusive 2" pneumatic pop-out pressure sensitive high-speed BestPack tape head.

Tape roll lengths: 1000 yd and 1500 yd.

Front interlock safety gates.

UL approved electrical parts.

Maintenance free, oil-less cylinders.

Options

Second timer for multi-able tabs on the single carton edge

Spare parts kit

Infeed/exit conveyor with L-bracket stabilizer

Heavy-duty dual locking casters

High-speed motor upgrade (up to 125 feet per minute)

Indexer (for fully automatic function)

Food grade 304 stainless steel

Low or no tape sensor and alarms

Spare tape head

Power & Air

Power: 110 Volt, 60Hz, 122W, 1.9 Amp

Air: 50 psi, 5 scfm

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

| Model | Machine Dimensions | Case Length | Case Width | Case Height | Conveyor Height | Cases per Minute | Shipping Weight |
|----------------|--------------------|-------------|--------------|---------------|-----------------|------------------|-----------------|
| MS1ETL22-2 | 41.5"L | 7.0" - ∞" | 1.72" - 5.5" | 4.0" - 21.75" | 23.5" - 30.0" | Up to 45 | 350 lbs |
| 2" Tape Head | 26.0"W | | | | | | |
| Top Left Edge | 62.25"-68.75"H | | | | | | |
| MS1ETR22-2 | 41.5"L | 7.0" - ∞" | 1.72" - 5.5" | 4.0" - 21.75" | 23.5" - 30.0" | Up to 45 | 350 lbs |
| 2" Tape Head | 26.0"W | | | | | | |
| Top Right Edge | 62.25"-68.75"H | | | | | | |

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.