



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MS20 Manual Bottom Only Uniform Case Sealer



At a Glance

- Seal carton bottoms for packing
- Two side belt drive
- Exclusive 2 inch or 3 inch pop-out pressure-sensitive high-speed tape heads
- Width adjustment can be mounted on either side of carton sealer
- Up to 40 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Quickly Seal Carton Bottoms

The BestPack MS20 bottom-only operator-fed case sealer is designed for uniform bottom carton closure applications.

The BestPack MS20 line incorporates 2" or 3" pop-out pressure-sensitive high speed tape heads with BestPack's patented tab adjustment.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Two side belt drive.

Adjustable bed height from 20.5" to 30.0".

Width adjustment can be mounted on either side of carton sealer.

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.

Heavy-duty frame.

UL approved electrical parts.

High-speed tape head.

Capable of interchanging 2" or 3" tape heads.

Electrical on/off box can be mounted on either side of carton sealer.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and

noise reduction arm.

Options

Spare parts kit

High-speed motor upgrade (up to 125 feet per minute)

Interlock safety gates

Infeed/exit conveyor with L-bracket stabilizer

Food grade 304 stainless steel

Heavy-duty locking casters

Spare tape head

Power & Air

Power: 110 Volts, 60 Hz

Air: None

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Conveyor Height	Cases per Minute	Shipping Weight
MS20-2 2" Tape Head	39.5"L 28.3"W 29.4"H	6.0" - ∞"	4.25" - 20.0"	20.5" - 30.0"	Up to 40	263 lbs
MS20-3 3" Tape Head	39.5"L 28.3"W 29.4"H	6.0" - ∞"	5.25" - 20.0"	20.5" - 30.0"	Up to 40	263 lbs
MS30-2 2" Tape Head	39.5"L 39.4"W 29.4"H	6.0" - ∞"	4.25" - 30.0"	20.5" - 30.0"	Up to 40	310 lbs
MS30-3 3" Tape Head	39.5"L 39.4"W 29.4"H	6.0" - ∞"	5.25" - 30.0"	20.5" - 30.0"	Up to 40	310 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.