



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MSBFT Semi-Auto Bottom Only Uniform Case Sealer



At a Glance

- Quickly tape carton bottoms
- Stainless steel T rail for durability and minimal carton friction
- Exclusive 2 inch or 3 inch pop-out pressure-sensitive high-speed tape heads
- Extended belt drive for positive carton feed
- Up to 15 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal Cartons More Easily than Hand Taping

The BestPack MSBFT uniform operator-fed, bottom only case sealer is designed to reduce operator time and fatigue when folding & sealing the bottom flaps of a carton. The quality of the seal and the appearance of the carton is greatly improved over hand taping.

This MSBFT bottom-only taper is perfect for when carton-forming volume has become too large to manually form and tape cartons, but not large enough to justify a fully-automatic carton erector/sealer.

The MSBFT bottom-only taper has two stations. The first station folds bottom flaps of the carton. The second station seals bottom flaps, and feeds the carton automatically on to a conveyor.

BestPack MSBFT line incorporates pop-out pressure-sensitive high speed tape head with BestPack's patented tab adjustment.

All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Heavy-duty frame.

Uniform bottom flap folder/bottom sealer.

Extended belt drive for positive carton feed.

Stainless steel T rail for durability and minimal carton friction as the carton is formed.

Operator can work from either side of the carton sealer.

Adjustable bed height from 23.5" to 30.0".

Tape roll lengths: 1000 yd, 1500 yd, 2000 yd.

UL approved electrical parts.

Capable of interchanging 2" or 3" tape heads.

Exclusive 2" or 3" pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

Options

Spare parts kit

High-speed motor upgrade (up to 125 feet per minute)

Food grade 304 stainless steel

Locking casters with support brackets

Long exit conveyor

Spare tape head

Infeed/exit conveyor with L-bracket stabilizer

Power & Air

Power: 110 Volts, 60 Hz

Air: None

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
MSBFT20-2 2" Tape Head	99.6"L 28.4"W 29.4"H	7.8" - 23.6"	7.8" - 19.6"	4.0" - ∞"	23.5" - 30.0"	Up to 15	350 lbs
MSBFT20-3 3" Tape Head	99.6"L 28.4"W 29.4"H	7.8" - 23.6"	7.8" - 19.6"	4.0" - ∞"	23.5" - 30.0"	Up to 15	350 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.