



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MSD-6 6-Inch Manual Side Drive Uniform Case Sealer



At a Glance

- Side belt drive
- Applies 6-inch tape
- Four adjustable legs for height modification
- Exclusive 2 inch or 3 inch pop-out pressure-sensitive high-speed tape heads
- Telescopic mast design
- Up to 40 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Quad-Belt Drive Provides Carton Stability and Effective Sealing

The BestPack MSD-6 semi-automatic uniform tape carton sealer is an operator fed adjustable carton sealer using 6-inch wide tape to seal the top and bottom of a carton. 6-inch wide tape helps with security, tamper protection, and pilferage prevention, and also effectively seals cartons that are overly heavy, over-filled, or otherwise difficult to keep sealed.

All BestPack case tapers are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance. The MSD-6 sealer also accepts 4", 3" and 2" tape heads with optional skid plate adapters.

Features

Heavy-duty 2mm CNC cut and welded frame including upper welded legs.

Side belt drive system with idler rollers behind the 1-piece die molded belts that also includes V-belt guide.

Accepts 6", 4", 3", and 2" pop-out BestPack high-speed tape heads.

Telescopic mast design with screw drive shafts and a unique 4 roller upper side compression unit.

Width/height adjustment handle can be mounted on either side of the carton sealer.

Adjustable bed height from 23.5" to 30.0".

Electrical on/off box can also be easily mounted on either side of the sealer (left side is standard).

Tape roll lengths: 1000 yd and 1500 yd.

Extra 4" carton height adjustment available on upper assembly.

Exclusive pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise.
Reduction arm.
Quality UL approved electrical parts.

Options

- Infeed/exit conveyor w/ L-bracket stabilizer
- Heavy-duty dual locking casters
- Spare parts kit
- High-speed motor upgrade (up to 125 feet per minute)
- 3 flap folder
- Interlock safety gates
- Motorized height and/or width adjustment
- Food grade 304 stainless steel
- Motorized assist tape heads when high speed motors and/or acrylic tapes are used

Power & Air

Power: 110 Volts, 60 Hz
Air: None

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
MSD22-6 6" Tape Head	39.5"L 32.8"W 70.3"H	6.0" - ∞"	8.25" - 20.0"	3.5" - 20.5"	23.5" - 30.0"	Up to 40	425 lbs
MSD22-6M 6" Tape Head	39.5"L 32.8"W 70.3"H	6.0" - ∞"	8.25" - 20.0"	3.5" - 20.5"	23.5" - 30.0"	Up to 40	425 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.