



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# BestPack MSD-EB Manual Side Drive Uniform Case Sealer



## At a Glance

- Side belt drive
- Pairs wells with a packing station
- Extended belt drives and 3 flap folders reduce operator repetitive motion
- Electrical box and handles mount on either side of sealer
- Seals up to 40 cases per minute

## Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Efficiently Grab, Flap Fold, and Seal in One Station

The BestPack MSD-EB sealer is a unique multi-purpose solution. Featuring a convenient top 3-flap folder and extended side-drive system, the MSD-EB enables a person to efficiently grab, flap fold, and seal a carton in one station. Dual telescopic masts allow for an extra 4" carton height extension on the upper assembly and two 110V UL-approved electric motors power the extended side belt drive.

All BestPack case tapers are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

## Features

Electrical on / off box can be mounted on either side of carton sealer.

Exclusive pop-out pressure sensitive high-speed tape head with patented tab adjustment and noise reduction arm.

3 flap folder automatically folds the top flaps of cartons.

Extended belt drives grabs carton without operator having to push the box into the sealer.

Side belt drive system.

Telescopic mast.

Extra 4" height adjustment available on upper assembly.

Adjustable bed height 23.5" to 30.0".

Width / height adjustment knobs can be mounted on either side of carton sealer.

Upper side compression unit.

Tape roll lengths 1000, 1500, 2000 yards.  
Heavy-duty frame.  
UL approved electrical parts.  
Capable of interchanging 2" and 3" tape heads.

## Options

Available in stainless steel  
Interlock safety gates  
Low-tape / no-tape monitoring  
Infeed / exit conveyors  
Heavy-duty casters  
High-speed options (up to 125 ft per min)

## Power & Air

Power: 110 Volts, 60 Hz  
Air: None

## Specifications

Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
59.0" x 28.3" x 59.6"	6.0" - ∞"	4.25" - 20.25"	3.38" - 20.5"	23.5" - 30.0"	Up to 40	492 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.