



## Professional Packaging Systems

2010 S. Great Southwest Parkway  
Grand Prairie, Texas 75051  
[www.ProPac.com](http://www.ProPac.com)

## Contact

Our Packaging Experts  
[solutions@propac.com](mailto:solutions@propac.com)  
888-318-0083

# BestPack MSL Manual Low Profile Uniform Case Sealer



## At a Glance

- Seal cartons as short as 2.5 inches high
- Four adjustable legs for height modification
- Exclusive 2 inch or 3 inch pop-out pressure-sensitive high-speed tape heads
- Telescopic mast design
- Up to 40 cases per minute

## Pricing

Call us at **888-318-0083**

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

## Seal Cartons as Short as 2.5" High

The BestPack MSL is an operator fed, adjustable carton sealer designed to effectively seal very low-profile boxes, in addition to the standard array of carton sizes. The MSL seals cartons a mere 2.5" high. The upper mast allows for an extra 4" carton height extension on the upper assembly.

The BestPack MSL tapers incorporate exclusive 2" or 3" pop-out pressure-sensitive high-speed tape heads with BestPack's patented tab adjustment. All BestPack units are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

## Features

Side belt drive.

Width/height adjustment handle can be mounted on either side of the carton sealer.

Seals cartons as low as 2.5" in height.

Upper side compression unit.

Adjustable bed height from 20.5" - 30".

Extra 4" carton height adjustment available on upper assembly.

3" model capable of interchanging 2" or 3" tape heads.

Tape roll lengths: 1000 yd, 1500 yd, and 2000 yd.

Heavy-duty frame.

UL approved electrical parts.

Electrical on/off box can be mounted on either side of the sealer.

Exclusive 2" or 3" pop-out pressure sensitive high speed tape head with patented tab adjustment and noise reduction arm.

## Options

- Spare parts kit
- High speed motor upgrade (up to 125 feet per minute)
- Locking heavy-duty casters
- Infeed/exit conveyor with L-bracket stabilizer
- 3-flap folder
- Interlock safety gates
- Food grade 304 stainless steel

## Power & Air

- Power: 110 Volts, 60 Hz
- Air: None

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

## Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
MSL22-2 2" Tape Head	56.8"L 33.5"W 71.3"H	6.0" - ∞"	5.7" - 21.0"	2.5" - 20.5"	20.5" - 30"	Up to 40	400 lbs
MSL22-3 3" Tape Head	56.8"L 33.5"W 71.3"H	6.0" - ∞"	6.7" - 21.0"	2.5" - 20.5"	20.5" - 30"	Up to 40	400 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.