



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

BestPack MTD Manual Top & Bottom Drive Uniform Case Sealer



At a Glance

- 4 belt drive: 2 top and 2 bottom belts
- Designed to handle tall unstable cartons
- Exclusive 2 inch or 3 inch pop-out pressure-sensitive high-speed tape heads
- Telescopic mast design
- Up to 50 cases per minute

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Seal Tall Unstable Cases with a 4-Belt Drive Taper

The BestPack MTD semi-automatic adjustable case sealer, engineered for the economical and effective operator-fed closure of difficult to seal cartons. With two belt drives at the top and two belt drives at the bottom of cartons, the MTD case taper is designed to handle tall unstable cartons.

The MTD comes standard with a manual self-centering mechanism that permits the operator to quickly center the carton and the tape. Dual telescopic masts allow for an extra 4" carton height extension on the upper assembly.

BestPack MTD case sealers incorporate 2" or 3" pop-out pressure-sensitive high speed tape heads with BestPack's patented tab adjustment.

All BestPack case tapers are available in standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

Features

Telescopic dual mast design.

Designed for uniform applications.

4-belt drive: 2 top and 2 bottom belts.

MTD22 adjustable bed height: 23.5" - 30".

MTD33 adjustable bed height: 25.8" - 30".

Extra 4" carton height adjustment available on upper assembly.

Height adjustment handle can be mounted on either side of the carton sealer.

Upper side compression unit.

Tape roll lengths: 1000 yd, 1500 yd, and 2000 yd.

Heavy-duty frame.

UL approved electrical parts.

Guide rail centering mechanism.

3" model capable of interchanging 2" or 3" tape heads.

Options

Spare parts kit

High-speed motor upgrade (up to 125 feet per minute)

Motorized height adjustment

Infeed/exit conveyor with L-bracket stabilizer

Interlock safety gates

Low tape or no tape sensor

Food grade 304 stainless steel

Power & Air

Power: 110 Volts, 60 Hz

Air: None

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.

Specifications

Model	Machine Dimensions	Case Length	Case Width	Case Height	Conveyor Height	Cases per Minute	Shipping Weight
MTD22-2 2" Tape Head	35.3"L 28.8"W 69.7"H	6.0" - ∞"	6.5" - 19.3"	4.0" - 20.0"	23.5" - 30"	Up to 40	345 lbs
MTD22-2H 2" Tape Head	35.3"L 28.8"W 69.7"H	6.0" - ∞"	6.5" - 19.3"	4.0" - 20.0"	23.5" - 30"	Up to 50	345 lbs
MTD22-3 3" Tape Head	35.3"L 28.8"W 69.7"H	6.0" - ∞"	7.5" - 19.3"	4.0" - 20.0"	23.5" - 30"	Up to 40	345 lbs
MTD22-3H 3" Tape Head	35.3"L 28.8"W 69.7"H	6.0" - ∞"	7.5" - 19.3"	4.0" - 20.0"	23.5" - 30"	Up to 50	345 lbs
MTD33-3 3" Tape Head	35.3"L 43.8"W 79.7"H	6.0" - ∞"	7.5" - 30.0"	4.0" - 30.0"	23.5" - 30"	Up to 40	375 lbs
MTD33-3H 3" Tape Head	35.3"L 43.8"W 79.7"H	6.0" - ∞"	7.5" - 30.0"	4.0" - 30.0"	23.5" - 30"	Up to 50	375 lbs

Please [contact Pro Pac](#) or call 888-318-0083 for your case sealing equipment.